

Plug-In

DESCRIPTION:

Highlighting a dedication to quality and integrity, the Sunlite product line includes light bulbs of LED, linear fluorescent, compact fluorescent, incandescent, HID metal halide, halogen, decorative, and specialty lamps. In addition, the Sunlite line includes various indoor and outdoor commercial, Industrial, and residential fixtures. Electrical products include extension cords, socket adapters, wall plates, receptacles and switches, dimmers, timers, surge protectors, and much more.

FEATURES:

-
-
-
-
-



SPECIFICATIONS:

General Characteristics

Bulb Shape	PLD
Nanometer	N/A
Ansi code	G24D
Average Rated Hours	50000
Finish	Frost
Base	G24D 2-Pin LED BASE (G24D)
Average Life Span Years	46
Dimmable	No
Dimming Type	Not Dimmable
Material	PC

Product Data

Case Unit Rate	12
Item UPC	653703888088

Electrical Characteristics

Watts	10
Volts	120-277
Equivalent Wattage	26
Power Factor	0.90@120VAC
Temperature	-20-45C
Ballast Factor	hybrid

Light Characteristics

Lumens Brightness	1050
Color Rendering Index CRI	80
CBCP	N/A
Emitted Color	CCT Selectable
Color Temperature Kelvin	30K/40K/50K
Beam Angle	120

Additional Features

Safety Rating Mark	UL Listed - Damp Location
Safety Rated For USA	Yes