

LED

4 ft. Direct Wire T5 Tube



FEATURES

- Meets DLC performance and efficiency criteria
- Equivalent to a 54-Watt fluorescent tube
- 4000 Kelvin cool white color temperature
- Frosted glass lens to evenly diffuse light
- UL listed for use in damp locations
- DLC® Part Number: PLTSP56214
- Mini Bi-Pin G5 base

APPLICATIONS

- Office spaces and conference rooms
- Classrooms and hallways
- Hospitals and lobbies



SKU#	Kelvin	Lumens	CRI	Wattage	Voltage	DLC?	Base	LED L70 Life Hours	Warranty
LEDT-10080	4000	3500	82	25	120-277	YES	Mini-Bi-Pin	≥100,000	5 Year

SPECIFICATIONS

DIMMABLE	YES	LUMENS	3,500
DLC LISTED	YES	VOLTAGE	120-277
SAFETY RATING	UL DAMP	LENS	FROSTED GLASS
CRI	82	BASE TYPE	MINI BI-PIN
COLOR	COOL WHITE	BALLAST TYPE	BALLAST BYPASS
COLOR TEMPERATURE	4000K	DIAMETER	0.74 IN.
LED L70 LIFE HOURS	≥100,000	LENGTH	45.79 IN.
WATTAGE	25 WATTS	FLUORESCENT EQUAL.....	54 WATT