



Color Selectable LED PL Lamps – Hybrid

DESCRIPTION

Reduce your energy costs by replacing CFL PL lamps with this more efficient color selectable LED PL lamp that operates with or without an existing compatible ballast.

FEATURES

- Frosted lens reduces visual glare
- Delivers up to 166 Lumens per Watt for highly efficient performance
- Light output varies depending on the color temperature selected; see Selectable Table for more information
- Replaces up to a 13W CFL lamp
- Universal burn position
- No rewiring or modifications of any kind required for plug-and-play (Type A) operation; must be used with a compatible ballast, see installation sheet for full list of compatible ballasts
- Can operate directly off line voltage for ballast bypass (Type B) operation; ballast must be removed and fixture rewired during installation; see installation instructions for more information
- Only operates on magnetic ballasts listed in compatibility list. See installation sheet for full list of compatible ballasts.
- Color temperature can be adjusted using the switch on the base of the bulb; see installation instructions for more information

LISTINGS

- UL Listed for damp locations
- IP20

PERFORMANCE

- CRI: 80
- CCT: 2700, 3000K, 3500K, 4000K, & 5000K
- LED L70 Life Hours: 50,000 hours

THERMAL

- – 4°F to 113°F (-20°C to 45°C) operating temperature

Project name	Type
Catalog number	
Comments	Voltage
Approved by	Date



WARRANTY

- 5-year limited warranty; see pltsolutions.com for warranty details

APPLICATIONS

- Recessed Cans
- Ceiling Fixtures
- Wall Sconces

PERFORMANCE	Power Consumption*	3, 5 Watt
	CRI	80
	CCT*	2700K, 3000K, 3500K, 4000K, 5000K
	LED L70 Life Hours	50,000
ELECTRICAL	Input Voltage	120-277V
	THD	20%
	Power Factor	0.9
	Surge Protection	500V
	Burn Position	Universal
CONSTRUCTION	Shape	PL
	Base	G23, GX23
	Lens	Plastic
	Finish	Frosted
LISTINGS	Certifications	UL Listed, IP20
	Environment	Damp Locations

* See Selectable Table for full breakdown

PERFORMANCE SUMMARY

Item #	Base	Wattage*	CCT*	Voltage	Replaces	CRI	Finish	LED L70 Life Hours	Burn Position
PLT-20335	G23	3	2700K/3000K/3500K/4000K/5000K	120-277V	5 to 9W CFL	80	Frosted	50,000	Universal
PLT-20336	GX23	5	2700K/3000K/3500K/4000K/5000K	120-277V	13W CFL	80	Frosted	50,000	Universal

*See Selectable Table for full breakdown


SELECTABLE TABLE

SKU	Wattage	CCT	Lumens	Efficacy
PLT-20335	3	2700K	407	136
		3000K	422	141
		3500K	435	145
		4000K	452	151
		5000K	458	153
PLT-20336	5	2700K	768	153
		3000K	803	161
		3500K	806	161
		4000K	830	166
		5000K	830	166

DIMENSIONS

PLT-20335

Length – 5.3"
Width – 1.26"



PLT-20336

Length – 7.1"
Width – 1.26"



WARNINGS

- Not for use with dimmers.
- Not for use in enclosed fixtures.