

**DESCRIPTION**

Replace existing fluorescent troffers with these LED ready troffers designed for use with direct wire LED T8 tubes.

FEATURES

- Cost-effective architectural recessed LED ready troffer
- One to one alternative LED solution for fluorescent troffers
- Utilizes 4 single-ended direct wire LED T8 tubes (Sold Separately)
- Perfect for general illumination and provides visual comfort with minimal glare

LISTINGS

- UL Listed for damp locations
- IP20
- RoHS

ELECTRICAL

- Input voltage: 120-277V
- Pre-wired non-shunted sockets

INSTALLATION

- Designed for recess mounting in T-grid or dropped ceilings; see installation instructions for more information

CONSTRUCTION

- Galvanized steel housing
- Acrylic lens

THERMAL

- -4°F to 104°F operating temperature

Project name	Type
Catalog number	
Comments	Voltage
Approved by	Date

**WARRANTY**

- 5-year limited warranty; see pltsolutions.com for warranty details

APPLICATIONS

- Conference Rooms
- Retail
- Offices
- Hospitality
- Healthcare
- Schools
- Receptions Areas
- Corridors
- Foyers

ELECTRICAL	Lamp Type (Not Included)	T8 Single End Direct Wire LED Lamps
	Number of Lamps	4
	Max. Wattage per Tube	24.5W
	Input Voltage	120-277V
CONSTRUCTION	Housing	Galvanized steel
	Lens	PMMA
	Base Power Supply	Hard wired for Single-ended Direct Wire T8 LED Lamps
	Finish	White
LISTINGS	Certifications	UL Listed, IP20, RoHS
	Operating Temperature	-4°F to 104°F
	Environment	Damp Locations

PERFORMANCE SUMMARY

Item #	Length	Width	Height	Max. Wattage per Tube	Voltage	Warranty	Compatible Lamps
PLT-80104	47.8"	23.8"	3.3"	24.5W	120-277V	5-years	Single-ended Direct Wire T8 LED Lamps

DIMENSIONS



DIMENSIONS:
Length – 47.8"
Height – 3.3"
Width – 23.8"
Weight – 19 lbs.