



Plusline Large (double ended)

Plusline Large 1000W R7s 230V 1CT/10

PlusLine Large flood delivers maximum light output to light up large areas like outdoor, buildings and shops.

Product data

General Information		Voltage (Nom)	
Cap-Base	R7S [R7s]	230 V	
Operating Position	P4 [Parallel +/-4D or Horizontal(HOR)]	Controls and Dimming	
Nominal Lifetime (Nom)	2000 h	Dimmable	Yes
Switching Cycle	8000X	Mechanical and Housing	
Rated Lifetime (Hours)	2000 h	Bulb Finish	Clear
Light Technical		Bulb Shape	T11 [T 11mm]
Luminous Flux (Nom)	21500 lm	Approval and Application	
Luminous Flux (Rated) (Nom)	21500 lm	Energy Consumption kWh/1000 h	1000 kWh
Correlated Color Temperature (Nom)	2900 K	Luminaire Design Requirements	
Luminous Efficacy (rated) (Nom)	21.5 lm/W	Bulb Temperature (Max)	900 °C
Color Rendering Index (Nom)	100	Pinch Temperature (Max)	350 °C
LLMF at End of Nominal Lifetime (Min)	80 %	Product Data	
Operating and Electrical		Full product code	871150049434401
Power (Nom)	1000 W	Order product name	Plusline Large 1000W R7s 230V 1CT/10
Lamp Current (Nom)	4.35 A	EAN/UPC - Product	8711500494344
Starting Time (Nom)	0.0 s	Order code	923932143203
Warm Up Time to 60% Light (Nom)	instant full light	Numerator - Quantity Per Pack	1
Power Factor (Nom)	1		

Plusline Large (double ended)

Numerator - Packs per outer box	10
Material Nr. (12NC)	923932143203
Net Weight (Piece)	0.016 kg

ILCOS Code	HDG//RS-1000-230-R7s-185,7
------------	----------------------------

Dimensional drawing



Product	D (max)	B (max)	B	B (min)	C (max)
Plusline Large 1000W R7s 230V 1CT/10	11 mm	187.3 mm	185.7 mm	184.1 mm	189.1 mm

DEBig 1000W R7s 230V T11 CL

