



# 48W LED Panel (2x4), 4000K

Order Code: PN62316

Model# PD24-48N-ANR-W00



### Description

The Venture Lighting LED panel series of luminaires are low profile, lightweight, and designed for long life and low maintenance. These are designed to quickly and easily upgrade existing fluorescent fixtures.

### Construction

The high performance LED source is mounted to ensure proper thermal management of the system. The design allows for a cooler running LED chip which leads to longer lifetime, better efficacy, and color consistency.

### Optics

The fixtures are designed to have low glare yet utilize high performance materials to maximize efficacy and achieve precise photometric distributions.

### Electrical

The power supply has a range of 120-277V, 50/60 Hz. 0-10V DC dimming capability is standard. The fixture is rated for damp and dry locations. Fixtures are IC-rated.

### Mounting

The fixture is designed for replacing fluorescent fixtures.

### Product Performance

Operating Temperature Range	-13°F to 113°F (-25°C to 45°C)
Wattage	48W
Lumen Output	5445
Correlated Color Temperature (CCT)	4000K
Color Rendering Index (CRI)	80+
Life Hours	50,000

### Physical Characteristics

Fixture Color	White
Width	23.7"
Length	47.7"
Height	1.9"
Panel Size	2x4
Weight	20.2 lbs

### Electrical Characteristics

Amperage Draw (Input Volts/Amps)	120/0.42 208/0.25 240/0.22 277/0.19
----------------------------------	-------------------------------------

### Regulatory Qualifications

cULus Listed

DLC Qualified - Model# PD24-48N-ANR-W00

IC-rated

### Accessories

KT18522 2X4 SURFACE MOUNT KIT, WHITE

KT18916 2x4 DRYWALL MOUNT KIT, WHITE

BB23468 - Battery Back-up



# Venture 48W LED Panel (2x4), 4000K

48W 2x4 LED Panel

