


LTR	REVISION	DATE	APPD
-	RELEASED (REF. N1145002)	01-18-11	



**NOTES:**

1. MTG HOLE DIA: 0.63"[16MM]
2. NON-RELAMPABLE REPLACEMENT FOR GE ET5 AND ET6
3. LENS MATERIAL: POLYCARBONATE (UL 94V-2)
4. SLEEVE MATERIAL: THREADED ROD - 6061-T6 ALUMINUM, CLEAR ANODIZE
5. NUT MATERIAL: ALUMINUM 6061T6
6. WASHER MATERIAL: NEOPRENE
7. ALL DIMS ARE IN INCHES [MILLIMETERS].



PNL-1145-201	RED	SUPER RED	250VDC	280VDC	0.004A	633	1.00W	0.073
PNL-1145-203	GREEN	AQUA GREEN	250VDC	280VDC	0.004A	525	1.00W	0.073
PNL-1145-205	WATER CLEAR	WARM WHITE	250VDC	280VDC	0.004A	3000K	1.00W	0.073
LEDTRONICS PART NO.	LENS COLOR	COLOR EMITTED	INPUT VOLTAGE	INPUT VOLTAGE	CURRENT (A)	$\lambda_P$ nm	POWER (WATTS)	WEIGHT (LBS)
			typ.	max	typ.		typ.	
<b>ELECTRICAL TEST</b>								

 LEDTRONICS, INC. 23105 KASHIWA COURT TORRANCE, CA 90505	-PROPRIETARY- This document contains Proprietary information of LEDTRONICS, INC. It may not be copied, used or disclosed for any purpose without the prior express written consent of LEDTRONICS, INC.		<b>TITLE</b> PNL-1145-20X					
	.XXX ± .010 TOLERANCE PER ANSI-Y14.5 .XX ± .025 (UNLESS OTHERWISE STATED) ANGLES ± 0',30' FRACT. ± 1/32		DWG NO N1145007	SCALE 1:1	SHEET 1 OF 1	DATE 01-18-11		
	CODE IDENT NO. 8Z410	DWG BY MM 01-18-11	CHK BY PL 01-20-11	QA	MFG	R&D		