

### FIELD-INSTALLABLE MOUNTING AND ACCESSORY OPTIONS

MOUNTING/ACCESSORY OPTIONS	IMAGE	ORDER SKU#	DIMENSIONS/NOTES
Safety Tether (optional)		Size 1X & 2X: 93159859G Min Order Quantity = 10	Cable length: 1m (39.4 in.) Cable Diameter: 2mm(.08 in.)
Wire Guard (optional)		Size 1X: 93159853G Size 2X: 93159854G Min Order Quantity = 10	Size 1X: H 4.8cm (1.9 in.); Dia 26.1 cm (10.2 in.) Size 2X: H 5.2cm (2 in.); Dia 31.5cm (12.4 in.)
90° Polycarbonate Refractor (optional)		Size 1X: 93159838G Size 2X: 93159839G Min Order Quantity = 1	Size 1X: H 16cm (6.3 in.); Dia 41cm (16.1 in.) Size 2X: H 16cm (6.3 in.); Dia 41cm (16.1 in.)
Polycarbonate Drop Lens (optional)		Size 1X & 2X: 93159840G Min Order Quantity = 1	Drop lens adds: H 4cm (1.6 in.)
90° Aluminum Reflector (optional)		Size 1X: 93159851G Size 2X: 93159852G Min Order Quantity = 5	Size 1X: H 16.1cm (6.3 in.); Dia 42cm (16.5 in.) Size 2X: H 18.2cm (7.1 in.); Dia 47.3cm (18.6 in.)
Wall Mount Bracket (optional)		Size 1X: 93159855G (HD03DPR) Size 2X: 93159856G (HB03DPR-Remote) Min Order Quantity = 10	Total Height of assembly from top of bracket to bottom of fixture: Size 1X: 15cm (5.9 in.) Size 2X: 17cm(6.7 in.)
PIR Sensor -New (optional)		Sensor: 93159862G Remote: 93159857G Min Order Quantity = 1	Notes: 1. Easy plug-and-play install to center face of fixture; maintains IP65 rating 2. Sensor requires remote if programming is desired 3. HB03DPR sensor is not compatible with 40W emergency battery
40W Emergency Battery		93161800	Dimensions: H: 10.78"; W: 5.57" Notes: 1. 120-277V only 2. 40W emergency battery is not compatible with HB03DPR sensor