Presented By: **Candela Corporation** Contact Phone: (800) 922-9226


Contact E-mail: sales@candelacorp.com



GE Lighting

43694 - Q150CL/MC GE T4





CAUTIONS & WARNINGS

Caution

Risk of Burn

- Allow lamp to cool before handling.
- Turn power off before installing lamp.
- · Lamp may shatter and cause injury if broken
- Dispose of lamp in a closed container.
- Do not use lamp if outer glass is scratched or broken.

Warning

- Risk of Electric Shock
- Turn power off before inspection, installation or removal.
- Unexpected lamp rupture may cause injury, fire, or property damage
- Use eye protection when handling lamp.
- Use in enclosed fixture rated for this product.
- Do not touch glass with bare hands.
- Do not use lamp if outer glass is scratched or broken.
- Do not exceed 110% of rated voltage.
- Lamp emits UV radiation which may cause eye/skin irritation.
- Avoid exposure of eyes and skin to unshielded lamp.

Risk of Fire

- Keep combustible materials away from lamp.
- Use in enclosed fixture rated for this product.

Customer Name: Project Name: Fixture Type:

GENERAL CHARACTERISTICS

Lamp Type	Halogen - Single-Ended
Bulb	Τ4
Base	Miniature Candelabra Screw
	(E11)
Filament	CC-8
Bulb Finish	Clear
Wattage	150
Voltage	120
Rated Life	2000 hrs

PHOTOMETRIC CHARACTERISTICS

Initial Lumens 2800

Color Temperature 2950 K Nominal Initial Lumens per Watt 18

Maximum Overall Length (MOL) Bulb Diameter (DIA) Bulb Diameter (DIA) (MAX) Light Center Length (LCL)

DIMENSIONS

3.0000 in(76.2 mm) 0.500 in(12.7 mm) 0.500 in(12.7 mm) 1.375 in(34.9 mm)

PRODUCT INFORMATION

Product Code Description ANSI Code Standard Package Standard Package GTIN Standard Package Quantity Sales Unit No Of Items Per Sales Unit No Of Items Per Standard Package UPC

43694 Q150CL/MC ETG Case 10043168436943 6 Unit 1 6

043168436946