

**Presented By:** Candela Corporation  
**Contact Phone:** (800) 922-9226  
**Contact E-mail:** sales@candelacorp.com


**Customer Name:**  
**Project Name:**  
**Fixture Type:**



GE  
Lighting

## 43695 - Q250MC

GE T4



### GENERAL CHARACTERISTICS

Lamp Type	Halogen - Single-Ended
Bulb	T4
Base	Miniature Candelabra Screw (E11)
Filament	CC-8
Bulb Finish	Frost
Wattage	250
Voltage	120
Rated Life	2000 hrs

### PHOTOMETRIC CHARACTERISTICS

Initial Lumens	4850
Color Temperature	2950 K
Nominal Initial Lumens per Watt	19

### DIMENSIONS

Maximum Overall Length (MOL)	3.1560 in(80.2 mm)
Bulb Diameter (DIA)	0.500 in(12.7 mm)
Bulb Diameter (DIA) (MAX)	0.500 in(12.7 mm)
Light Center Length (LCL)	1.625 in(41.3 mm)

### PRODUCT INFORMATION

Product Code	43695
Description	Q250MC
ANSI Code	ESM
Standard Package	Case
Standard Package GTIN	10043168436950
Standard Package Quantity	6
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard	6
Package	
UPC	043168436953

### CAUTIONS & WARNINGS

#### Caution

- Risk of Burn
  - Allow lamp to cool before handling.
  - Turn power off before installing lamp.
- Lamp may shatter and cause injury if broken
  - Dispose of lamp in a closed container.
  - Do not use lamp if outer glass is scratched or broken.

#### Warning

- Unexpected lamp rupture may cause injury, fire, or property damage
  - Use eye protection when handling lamp.
  - Use in enclosed fixture rated for this product.
  - Do not touch glass with bare hands.
  - Do not use lamp if outer glass is scratched or broken.
  - Do not exceed 110% of rated voltage.
- Risk of Fire
  - Keep combustible materials away from lamp.
  - Use in enclosed fixture rated for this product.
- Lamp emits UV radiation which may cause eye/skin irritation.
  - Avoid exposure of eyes and skin to unshielded lamp.
- Risk of Electric Shock
  - Turn power off before inspection, installation or removal.