



CLEANLIFE®

LED Drivers

Features:

- 12V or 24V Constant Voltage Design
- Power Ratings from 10~100W
- Universal AC input 100~277VAC
- Operating Temperature: -25°C~+50°C
- Overload, Over-Voltage, Short-Circuit, and Over-Temperature protections
- Typical Efficiency: 88% (±1%)
- 100% full load burn-in test
- IP-66 Protection, Outdoor Rated
- 5-Year Manufacturer's Limited Warranty
- CE, UL, SAM Certified, RoHS compliant



CUSTOM QUICK CONNECTOR OPTIONS AVAILABLE!



ORDERING INFORMATION

Part No.	Glantz Code	Description	Dimensions (Inches) L x W x H	UL/SAM	Class 2
VELCLP1012	QCLPS101266	CLEANLIFE® 10W 12V Power Supply	4.65" x 1" x 1.08"	Yes	Yes
VELCLP1024	QCLPS102466	CLEANLIFE® 10W 24V Power Supply	4.65" x 1" x 1.08"	Yes	Yes
VELCLP1512	QCLPS151266	CLEANLIFE® 15W 12V Power Supply	5.83" x 1" x 1.08"	Yes	Yes
VELCLP1524	QCLPS152466	CLEANLIFE® 15W 24V Power Supply	5.83" x 1" x 1.08"	Yes	Yes
VELCLP2012	QCLPS201266	CLEANLIFE® 20W 12V Power Supply	6.38" x 1" x 1.08"	Yes	Yes
VELCLP2024	QCLPS202466	CLEANLIFE® 20W 24V Power Supply	6.38" x 1" x 1.08"	Yes	Yes
VELCLP3012	QCLPS301266	CLEANLIFE® 30W 12V Power Supply	5.35" x 1.77" x 1.08"	Yes	Yes
VELCLP3024	QCLPS302466	CLEANLIFE® 30W 24V Power Supply	5.35" x 1.77" x 1.08"	Yes	Yes
VELCLP4012	QCLPS401266	CLEANLIFE® 40W 12V Power Supply	5.67" x 1.85" x 1.34"	Yes	Yes
VELCLP4024	QCLPS402466	CLEANLIFE® 40W 24V Power Supply	5.67" x 1.85" x 1.34"	Yes	Yes
VELCLP6012	QCLPS601266	CLEANLIFE® 60W 12V Power Supply	5.67" x 1.85" x 1.34"	Yes	Yes
VELCLP6024	QCLPS602466	CLEANLIFE® 60W 24V Power Supply	5.67" x 1.85" x 1.34"	Yes	Yes
VELCLP10012	QCLPS1001266	CLEANLIFE® 100W 12V Power Supply	8.27" x 2.81" x 1.79"	Yes	No
VELCLP10024	QCLPS1002466	CLEANLIFE® 100W 24V Power Supply	8.27" x 2.81" x 1.79"	Yes	Yes

To order, call or visit us online today!
1.866.NGLANTZ (645.2689) • nglantz.com

