



**Product Number:** 49869

**Order Abbreviation:** QHE 2x59T8/UNV ISL-SC

**General Description:** 2-lamp 59wT8 (8') High Efficiency Instant Start electronic ballast, universal voltage, low ballast factor, 10-pk.

Product Information	
Abbrev. With Packaging Info.	QHE2X59T8UNVISLSC 120-277V 10/CS 1/SKU
Ballast Factor	0.77
Ballast Height H (in)	1.1810
Ballast Length L (in)	9.4690
Ballast Width W (in)	1.6810
Circuit Type	Parallel
Family Brand Name	QUICKTRONIC High-Efficiency
Input Current (Amps)	0.00
Nominal Voltage (V)	120-277V
Number of Lamps	2
Open Circuit Voltage (V)	840V
Power Factor	>0.98
Primary Lamp Type	FO96T8 XP (59W)
Sound Rating	A
Starting Method	Instant Start
Starting Temperature - Fahrenheit	0
Starting Temperature - Celsius	-18
Total Harmonic Distortion (THD)	<10%
Wiring Method	Leads
Max Case Temperature	70°C



**QUICK 60+**  
ELECTRIC BALLASTS

#### Footnotes

- Data based on primary lamp types. See OSRAM SYLVANIA System Performance Guide for data on other lamp combinations.
- 70C Max Case Temperature
- UL Listed Class P, Type 1 Outdoor
- Insulate unused leads
- Ground ballast case
- Install in accordance with National Electric Codes
- Complies with FCC 47 CFR Part 18, Non-Consumer
- ANSI 62.41 Cat. A Transient Protection
- Class A Sound Rating.
- Minimum Starting Temperature: 0F/-18C.
- Input Frequency: 50/60Hz.
- High power factor
- Minimum starting temperature: 60 F / 16 C with SS lamps
- Cutout Lampholder
- Insulate unused leads individually for 840V