



**Product Number:** 50237

**Order Abbreviation:** QHE 2x59T8/UNVISN-SC-B

**General Description:** 2-lamp 59wT8 (8') High Efficiency Instant Start electronic ballast, universal voltage, normal ballast factor, banded 10-pk

Product Information	
Abbrev. With Packaging Info.	QHE2X59T8UNVISNSCB 10/CS 1/SKU
Ballast Height H (in)	1.1810
Ballast Length L (in)	9.4690
Ballast Width W (in)	1.6810
Family Brand Name	QUICKTRONIC High-Efficiency
Input Current (Amps)	0.00
Nominal Voltage (V)	120.00
Nominal Voltage (V)	120-277V
Total Maximum Wattage	109



QUICK 60+  
ELECTRONIC BALLASTS

Footnotes

- Data based on primary lamp types. See OSRAM SYLVANIA System Performance Guide for data on other lamp combinations.
- 70C Max Case Temperature
- UL Listed Class P, Type 1 Outdoor
- Ground ballast case
- Install in accordance with National Electric Codes
- Complies with FCC 47 CFR Part 18, Non-Consumer
- ANSI 62.41 Cat. A Transient Protection
- Class A Sound Rating.
- Minimum Starting Temperature: 0F/-18C.
- Input Frequency: 50/60Hz.
- High power factor
- Minimum starting temperature: 60 F / 16 C with SS lamps
- Cutout Lampholder
- CSA certified.
- ANSI C82.11 where applicable.
- NO PCB (Polychlorinated Biphenyl)
- Insulate unused leads individually for 840V
- Remote mounting up to 20 feet