


# QWIK MOD 2 BLUE™

Better coverage with a wider optic—accomplish more with our NEW Qwik Mod™ Series.



## SPECIFICATIONS

Beam Angle	170° Ultra-Wide Low Dome Batwing Optic with Diamondback Optic Lens Technology
Certifications	UL & cUL Recognized (SAM Manual), CE, RoHs
Dimensions	0.69"W x 2.2"L x 0.25"H
Efficacy	See Product Options
Fastening	Peel & Stick / Mechanical Screw Hole
Input	12VDC
Intensity	See Product Options
Max Mods (Series)	See Product Options
Operating Temp	-25° to +60°C
Packaging	44.71 ft. (76 mods) per bag or 536.52 ft. (912 mods) per case
Power	See Product Options
Power Supply	P-LED 12VDC
Protection Grade	IP68
Run Footage	See Product Options
Spacing	1.7 mods/ft. (fully stretched)
Warranty	5 Year Product / 5 Year Limited Labor

## FEATURES

- Diamondback 170° Optic Lens
- Integrated aluminum heatsink
- Snap & Peel Qwik Release Tab
- More light diffusion with a wider batwing resulting in better coverage

## WIRING DETAILS

White/Red	Positive
White/Black	Negative

## RECOMMENDED COVERAGE CHART

Depth	Max. Stroke	Row Spacing	Product
	Single Row	Multi-Rows O.C.	
3"	8"	4" at 3 mods/ft	QM2 Blue
4"	12"	7" at 2 mods/ft	QM2 Blue
5"	16"	10"	QM2 Blue
6"	18"	10"	QM2 Blue

Note: Product and depth may vary depending on face material and desired brightness.

## PRODUCT OPTIONS

Color	Wavelength	Efficacy	Intensity	Power	Max. Mods (Series)	Run Footage	Part Number
Blue	460 nm	12.31 LM/W	10 LM/Mod (17 LM/FT)	0.8 W/MOD (1.36 W/FT)	22.35 ft (38 mods)	44.71ft (76 mods)	PL-QM2-BL17-P

