



Product Number: 49927

Order Abbreviation: QT 2X32T8/347 ISH-SC

General Description: QT2x32T8347ISHSC 2-lamp 32wT8 Instant start electronic ballast, 347V, high ballast factor, 10-pk

Product Information

Abbrev. With Packaging Info.	QT2X32T8347ISHSC
Ballast Factor	1.20
Ballast Height H (in)	1.1810
Ballast Length L (in)	9.4690
Ballast Width W (in)	1.6810
Circuit Type	PARALLEL
Family Brand Name	QUICKTRONIC
Input Current (Amps)	0.00
Nominal Voltage (V)	347.00
Nominal Voltage (V)	347V
Number of Lamps	2
Open Circuit Voltage (V)	<600V
Power Factor	>0.97
Primary Lamp Type	FO32/XP
Sound Rating	A
Starting Method	INSTANT START
Starting Temperature - Fahrenheit	0
Starting Temperature - Celsius	-18
Total Harmonic Distortion (THD)	<20%
Wiring Method	LEADS
Max Case Temperature	70°C
Total Maximum Wattage	80



Footnotes

- Data based on primary lamp types. See OSRAM SYLVANIA System Performance Guide for data on other lamp combinations.
- Remote Mounting up to 18 feet
- 70C Max Case Temperature
- Minimum Starting Temperature: 0F/-18C.
- Input Frequency: 60Hz.