



**Product Number:** 51425

**Order Abbreviation:** QTP 2X32T8/UNV PSX-TC

**General Description:** 2-lamp 32wT8 Programmed Rapid Start electronic ballast, universal voltage, 0.71 ballast factor, 10-pk

#### Product Information

|                                   |                          |
|-----------------------------------|--------------------------|
| Abbrev. With Packaging Info.      | QTP2X32T8UNVPSXTC        |
| Ballast Factor                    | 0.71                     |
| Ballast Height H (in)             | 1.0240                   |
| Ballast Length L (in)             | 9.4760                   |
| Ballast Width W (in)              | 1.6810                   |
| Circuit Type                      | SERIES                   |
| Family Brand Name                 | QUICKTRONIC Professional |
| Input Current (Amps)              | 0.00                     |
| Nominal Voltage (V)               | 120.00                   |
| Nominal Voltage (V)               | 120-227V                 |
| Number of Lamps                   | 2                        |
| Open Circuit Voltage (V)          | <600V                    |
| Power Factor                      | >0.98                    |
| Primary Lamp Type                 | FO32/XP                  |
| Sound Rating                      | A                        |
| Starting Method                   | Programmed Rapid Start   |
| Starting Temperature - Fahrenheit | 0                        |
| Starting Temperature - Celsius    | -18                      |
| Total Harmonic Distortion (THD)   | <10%                     |
| Wiring Method                     | Leads                    |
| Max Case Temperature              | 70°C                     |
| Total Maximum Wattage             | 47                       |



#### Footnotes

- Data based on primary lamp types. See OSRAM SYLVANIA System Performance Guide for data on other lamp combinations.
- Product is a kit containing the core & coil, capacitor, ingitor (where required), brackets and mounting hardware
- Remote Mounting up to 18 feet
- Remote Mounting up to 12 feet
- Remote Mounting up to 10 feet
- Complies with FCC 47 CFR Part 18, Non-Consumer
- Input Frequency: 60Hz.
- Wiring diagram applies to instant start standard, low power (LP), PLUS, and HD10 ballast types.
- Oil Filled Capacitor
- Product contains installation instructions