



Product Number: 51386

Order Abbreviation: QTP 2X42CF/UNV DALI

General Description: 2-Lamp Universal Voltage 100-3% electronic DALI dimming ballast for 42W DT/E lamps

Product Information

Abbrev. With Packaging Info.	QTP2X42CFUNVDALI 10/CS 1/SKU
Ballast Factor	1.00
Ballast Height H (in)	1.3500
Ballast Length L (in)	4.9500
Ballast Width W (in)	2.9300
Circuit Type	Series
Family Brand Name	QUICKTRONIC Professional
Input Current (Amps)	0.00
Nominal Voltage (V)	120.00
Nominal Voltage (V)	120-277V
Number of Lamps	2
Power Factor	>0.95
Primary Lamp Type	CF42DT/E
Sound Rating	A
Starting Method	Programmed
Starting Temperature - Fahrenheit	50
Starting Temperature - Celsius	10
Total Harmonic Distortion (THD)	<10%
Total Maximum Wattage	92



QUICK60+™
ELECTRONIC BALLAST

Footnotes

- Data based on primary lamp types. See OSRAM SYLVANIA System Performance Guide for data on other lamp combinations.
- 75C Max Case Temperature
- Install in accordance with National Electric Codes
- Complies with FCC 47 CFR Part 18, Non-Consumer
- ANSI 62.41 Cat. A Transient Protection
- Class A Sound Rating.
- Input Frequency: 50/60Hz.
- Minimum Starting Temperature: 50F/10C.
- High power factor