

Fixture Type: _____
 Catalog Number: _____
 Project: _____
 Location: _____

Lotos 4" & 6" Round

Downlight 5CCT

Model	Beam	Color Temp & CRI	Lumens	Finish
<input type="radio"/> R6ERDR	<input type="radio"/> W	2700K/3000K/3500K/4000K/5000K - 90	1200	<input type="radio"/> WT White

Example: **R6ERDR-W9CS-WT**
 For custom requests please contact customs@wacighting.com

DESCRIPTION

The wafer-thin Lotos LED Recessed Kit with remote driver combines high quality light output and efficiency while eliminating the need for a large housing. This innovative design can be installed easily as a remodel or new construction with an optional frame-in kit sold separately. Lotos is available in a downlight version for general ambient lighting and an adjustable version with a gimbal that pivots 360 degrees on a hinge. Now available with 5-CCT options.

FEATURES

- 5-CCT Switchable between 2700K and 5000K
- Multiple LED array for uniform illumination
- Driver included
- 5 year warranty

SPECIFICATIONS

Color Temp:	2700K/3000K/3500K/4000K/5000K
Input:	120 -277 VAC,50/60Hz
CRI	90
Dimming:	ELV: 100-5% , TRIAC: 100-5%
Rated Life:	50,000 Hours
Mounting:	Heavy gauge retention clips secures fixture to ceiling
Standards:	ETL, cETL, Title 24 JA8 Compliant, Wet Location Listed
Construction	Steel with frosted TIR lens




FINISHES:



White


LINE DRAWING:



Lotos 4" & 6" Round Downlight 5CCT

Fixture Type: _____
Catalog Number: _____
Project: _____
Location: _____

ACCESSORIES

	<i>Model</i>	<i>Description</i>	<i>Finish</i>
	RER-FRAME	Lotos	