


MODEL CODING AND OUTPUT RATINGS

	Model Number	Pout Max (W)	Iout (mA)	Vout Min (V _{DC})	Vout Max (V _{DC})	Vout No_Load
10 to 30W Housing						
10 - 15W	RCL010-0250A	10.5	250	24	42	50
	RCL015-0300A	12.6	300	24	42	50
	RCL015-0350A	14.7	350	24	42	50
	RCL015-0350B	11.2	350	21	32	41.6
	RCL015-0440A	15.0	440	24	34	44.2
	RCL015-0440B	11.0	440	19	25	32.5
16 - 20W	RCL020-0350A	19.6	350	40	56	60
	RCL020-0450A	18.9	450	24	42	50
	RCL020-0500A	16.0	500	21	32	41.6
	RCL020-0600A	16.2	600	20	27	35
	RCL020-0700A	16.8	700	14	24	31.2
21 - 30W	RCL030-0500A	21.0	500	24	42	50
	RCL030-0550A	23.1	550	24	42	50
	RCL030-0620A	26.0	620	24	42	50
	RCL030-0700A	22.4	700	21	32	41.6
	RCL030-0700B	29.4	700	24	42	50
	RCL030-0700C	27.3	700	27	39	50
	RCL030-0900A	24.3	900	20	27	35
	RCL030-0900B*	28.8	900	21	32	41.6
	RCL030-1100A	29.7	1100	20	27	35



*This product is only UL approved, no CB and no ENEC.

	Model Number	Pout Max (W)	Iout (mA)	Vout Min (V _{DC})	Vout Max (V _{DC})	Vout No_Load
31 to 50W Housing						
31 - 40W	RCL040-0700B	39.2	700	40	56	60
	RCL040-0800A	33.6	800	24	42	50
	RCL040-0850A	35.7	850	24	42	50
	RCL040-0900A	37.8	900	24	42	50
	RCL040-0940A	40.4	940	32	43	50
41 - 50W	RCL050-1050A	44.1	1050	24	42	50
	RCL050-1200A	50.4	1200	24	42	50
	RCL050-1400A	44.8	1400	21	32	41.6
	RCL050-1400B	47.6	1400	24	34	44.2

