

# PRODUCT DATASHEET

## RT VALUE 5/6" 3000K 700LM BA

DOWNLIGHT RETROFIT VALUE | Downlight Retrofit with static CCT and wattage



### Areas of application

- Residential
- Bedrooms
- Kitchens
- Bathrooms

### Product features

- Integrated white trim, E26 medium base socket adapter
- Fixed wattage and CCT
- Available in 120VAC
- Up to 88 LPW
- Energy savings up to 88 %
- Flicker-free dimming, phase-cut down to 10 %
- Color trim rings available as optional accessory

## TECHNICAL DATA

### Additional product data

Ordering Abbreviation	RT561A700ST930BAWHE26
Abbrev. With Packaging Info.	RT561A700ST930BAWHE26 6/CS 1/SKU
SKU UPC	0046135628658
NAED	62865
Family Brand Name	Value Class
General Description	Value Class Downlight for 5/6" can, 600lm, 120V, > 90 CRI, 3000K, baffle finish, w/E26 adaptor. Wet rated with plastic housing.Title 20/24Compliant and Energy Star Listed
Warranty	3 years

### Electrical data

Nominal Wattage	8.00 W
Nominal voltage	120.00 V
Power factor	≥0.90
Total Harmonic Distortion	< 20 %

### Photometrical data

Lumens	700 lm
Efficacy	80 lm/W
Color Temperature/CCT	3000 K
Color Rendering Index (CRI)	90
Luminaire Type	Downlight

### Dimensions & Weight

Diameter	7.36 in
Height	2.76 in
Product weight	0.44 lb

### Materials & Colors

Luminaire Finish	White
Housing color	White
Housing	Polycarbonate (PC)
Mercury content	0.0 mg

### Application & Mounting

Dimming	Yes
Type of Dimming	PHASE CUT
Mounting	Recessed

Replaceable light source	No
--------------------------	----

### Lifespan

Average Rated Life (hr)	25000
-------------------------	-------

### Logistical data

SKU Qty	1
Case Qty	6
Case Length (in)	15.472
Case Width (in)	9.882
Case Depth (in)	8.228
Case Cube (ft)	0.728
Case Weight (lbs)	4.187
SKU UPC	0046135628658
Pallet Qty	432



### Certificates & Standards

Certification Listing	RoHS / FCC / cULus
Replaceable light source (EPREL)	Not replaceable
Energy Star Rated	X

### Safety advice

- Suitable for indoor dry, damp and wet locations.
- For use in housings that can structurally support a lamp weighing one pound.
- RT5/6 designed to install in standard 5" and 6" insulated and non-insulated housings.
- Not intended for use with emergency light luminaires or exit lights.

### DOWNLOAD DATA

	Spec Sheets and Product Documents	Document name
	Extended installation guide	Value Class Downlight Installation Guide
	Product Family Spec Sheet	SCREW-BASE DOWNLIGHTS

### DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.