

\*Call for custom lamp / custom base or OEM project requests



Image	Order Code	Description	Other Detail	V	W	Base	Life Hr	Lumen	CP	MOL (mm)	LCL (mm)	Dia (mm)	Bulb Shape	Filament
A-1-1962DZ	A-1962DZ	JC 8.5V 62W Wire Terminal (1962DZ)	1962DZ	8.5	62	Wire Terminal	150		80	1.14in	0.285in	11	T-3	C-6
A-1-1962TY	A-1962TY	JC 8.5V 62W Wire Terminal(7.75") (1962TY)	1962TY	8.5	62	Wire Terminal(7-3/4")	50		110	1.14in	0.285in	11	T-3	C-6
A-1-1974	A-1974	JC 6V 20W Wire Terminal (1974)	1974	6	20	Wire Terminal	10000		10	1.14in	0.285in	11	T-3	C-6
A-2	A-6517	J 10V 100W Metal Base (1978X)	1978X	10	100	Metal Base	1000	1633	130	54.6(2.15in)		9	T21/2	C-8
A-3	A-1975	JC 12.8V 25W Double Slide (1975)	1975	12.8	25	Double Slide	500	314	25	29.7(1.17in)	11.2(0.41in)	11	T-3	C-6
A-4	A-6519	J 28V 100W Metal Sleeve (1970X)	1970X	28	100	Metal Sleeve	2000	1260	140	57.1(2.25in)		9	T21/2	CC-8
A-4	A-1964	J 28V 150W Metal Sleeve (1964)	1964	28	150	Metal Sleeve	1000		230	2.25in		11	T-3	CC-8
A-4	A-6527	J 28V 150W Metal Sleeve (1967)	1967	28	150	Metal Sleeve	1000	2600	210	57.1(2.25in)		9	T21/2	CC-8
A-5	A-6521	JC 28V 75W BA15S (1982)	1982	28	75	BA15s	2000	1300	110	48.0(1.88in)	27.0(1.06in)	11	T-3	CC-8
B-1	A-1959	J 28V 150W Tab (1959)	1959	28	150	Tab	300		240	2.25in	0.75in	13.5	T-4	CC-6
B-2	A-1945	JC 32V 200W Two Pin (1945)	1945	32	200	Two Pin	200		360	57.15(2.25in)	33.27(1.31in)	13.5	T-4	CC-6
B-3	A-1946	28V 250W Two Pin w/leads (1946)	1946	28	250	Two Pin w/Leads	50		660	1.46in	0.87in	11	T-3	CC-6
B-6	TBD	JC 28V 250W Two Pin w/leads (2586)	2586	28	250	Two Pin Leads	100		600	1.9in	1.3in	13.5	T-4	CC-6
C-13	A-6511	JC 12V 125W 10H BA15d (6511)	6511	12V	125	BA15d	750	2400	191	54.0(2.125in)	27.5(1.08in)	11	T3	C-8
C-13	A-6513	JC 24V 150W 5H BA15d		24V	150	BA15d								
C-13	A-6503	JC 28V 150W BA15d (6503)	6503	28V	150	BA15d	750	3300	263	54.0(2.125in)	27.5(1.08in)	11	T3	CC-8
C-3-SO14040	S-01026	JC 12V 20W GY9.5 (S014040)	S014040	12V	20	GY9.5	2000	300	24	51.0(2in)	30	11	T3	C-6
NA	A-1912	12V 125W BA15D (1912)	1912	12	125	BA15d	1000		191	1.93in	1.14in	13.5	T-4	CC-8
NA	A-6515	JC 26V 150W 5H BCD		26V	150	BA15d								
NA	A-6527L	JC 28V 10.5W BA9s BT		28V	10.5	BA9s/Black Top	2500		130 lm	1.3in	0.59in	9	T2	C-8
NA	A-6530L	JC 28V 10.5W BA9s CL		28V	10.5	BA9s/Clear Top	2500		130 lm	1.3in	0.59in	9	T2	C-8