



Shown actual size: Skylark dimmer and 1-gang Claro wallplate in White (WH).

Product family features

- Rocker switch returns light to light level indicated by slider on preset dimmers
- Slide up to brighten, down to dim
- LED+ models available
- Coordinating Claro and Stainless Steel wallplates only available separately
- All models must be derated unless otherwise noted. Visit lutron.com/multigang for more information.

Control types

- Single-pole (1 location)
- 3-way or 4-way (2 or more locations)

Direct load type compatibility

- Dimmable LED/CFL lighting (screw-base)
- Incandescent/halogen lighting
- Magnetic low-voltage lighting
- Electronic low-voltage lighting
- LED lighting
- Fluorescent lighting
- Ceiling fans
- Ceiling fan/lights

Load type requiring load interface

- Neon/cold cathode lighting

Lighting load interfaces may be applicable for some additional load type, voltage, and capacity combinations. For additional information see "Lighting Load Interfaces."

Available finishes

Use **BOLD** color code in model number (Example: S-600P-**GR**)
Gloss



Metal wallplates*



SS
Stainless Steel

* Stainless Steel metal wallplate only available separately and includes black plastic trim/adaptor, visible from side. Match with separate Black (BL) control.

Dimmers



- Preset models include rocker switch to return to light level indicated by slider
- Slide up to brighten, down to dim
- LED+ dimmer provides reliable dimming of dimmable LEDs/CFLs, as well as halogens and incandescents

Dimmable LED/CFL (screw-base) dimmer
Incandescent/halogen dimmer

LED+ dimmer with on/off switch

3-way/single-pole	SCL-153P- XX ¹
-------------------	----------------------------------

120V 150W (LED/CFL),
600W (Inc)

Visit lutron.com/LEDfinder for our online compatibility tool.

Adjustable low-end trim.

Incandescent/halogen dimmers

Dimmers with on/off switch	
Single-pole	S-10P- XX ¹
120V 1000W	
3-way	S-103P- XX ¹
120V 1000W	

Slide-to-off dimmers

Single-pole	S-1000- XX ¹
120V 1000W	

Dimmers with on/off switch and locator light

Single-pole	S-10PNL- XX ¹
120V 1000W	
3-way	S-103PNL- XX ¹
120V 1000W	

Magnetic low-voltage dimmers

Dimmers with on/off switch	
Single-pole	SLV-600P- XX ¹
120V 600VA (450W)	
3-way	SLV-603P- XX ¹
120V 600VA (450W)	

The stated VA (volt-ampere) rating includes the magnetic transformer heat losses and the lamp load. The stated W (watt) rating is the maximum lamp wattage based on assumed 20% transformer loss.

Electronic low-voltage dimmers

Dimmers with on/off switch*	
Single-pole	SELV-300P- XX ¹
120V 300W	
3-way	SELV-303P- XX ¹
120V 300W	

3-wire LED driver/fluorescent ballast dimmers

Dimmers with on/off switch*	
Single-pole	SF-10P- XX ¹
120V 8A	
Single-pole	SF-12P-277- XX ¹
277V 6A	
3-way	SF-103P- XX ¹
120V 8A	
3-way	SF-12P-277-3- XX ¹
277V 6A	

No derating required if ganged.
Adjustable low-end trim.

Tu-Wire fluorescent ballast dimmer

Dimmer with on/off switch	
3-way/single-pole	SFTU-5A3P- XX ¹
120V 5A	

Compatible with Advance Mark X and Sylvania POWERSENSE fluorescent ballasts, in addition to Lutron Tu-Wire.

XX¹: Gloss color codes

XX¹: Gloss color codes
Wallplates not included. Order separately.

* Requires neutral wire connection