



Designer

- Non-Corrosive
- Composite Construction
- Optional Photocell or Security Sensor (S85V Only)
- Mounting Hardware Included

GUIDE CODE: S85VF-BK-PC

ITEM #	DIFFUSER	LIGHT SOURCE	CCT	COLOR	OPTIONS
S85V	ACRYLIC C-Clear F-Frost	E26 MEDIUM BASE	C-4K W-3K	BK-Black WH-White BZ-Bronze	PC-Photocell S-Security Option Includes Motion Sensor & Photocell Combo
		(1) 40W MAX Medium Base LE26-9.5W; 800lm (E26 LED Lamp) †			
		120V LIGHTWAVE LED (Frost lens only)			
		LR12-13W; 1,000lm 80CRI LR15-15W; 1,400lm 80CRI LT12-12W; 1,040lm 90CRI LT15-16W; 1,400lm 90CRI			

GUIDE CODE: S85TC-BZ

ITEM #	DIFFUSER	LIGHT SOURCE	CCT	COLOR
S85T	ACRYLIC C-Clear F-Frost	E26 MEDIUM BASE	C-4K W-3K	BK-Black WH-White BZ-Bronze
		(1) 60W MAX Medium Base LE26-9.5W; 800lm (E26 LED Lamp) †		
		120V LIGHTWAVE LED (Frost lens only)		
		LR12-13W; 1,000lm 80CRI LR15-15W; 1,400lm 80CRI LT12-12W; 1,040lm 90CRI LT15-16W; 1,400lm 90CRI		

† Lamp included. All posts and post options sold separately. Spec sheets and IES files available online. Specifications subject to change without notice. LED option information on page 6.



COMPANION
349 Pier Mount Adaptor Available (see page 85)