

PRODUCT FOCUS DIMMAX & DIMMAX FLOOD

Compact Fluorescent Lamp



MLS15EADWW★

6,000 Hour
(7) 6762701504 (5)*



MLS25EADWW★

6,000 Hour
(7) 6762701104 (7)*



SKR315FLDWW★

6,000 Hour
(7) 6762733011 (7)*

SKR420FLDWW★

8,000 Hour
(7) 6762712212 (5)*

DIMMAX SPECIFICATIONS

Watts	Order Code	Description	Incandescent Equivalent	Lumens	Lamp Life (Hrs)	Pack Type	Case Pack	Dimensions (W" x MOL")	K
★ 15	01504	MLS15EADWW Dimmable E26	60	900	6,000	Box	12	2.4 x 5.4	2700
★ 25	01104	MLS25EADWW Dimmable E26	100	1600	6,000	Box	12	2.4 x 6	2700
★ 15	33011	SKR315FLDWW Dimmable E26	65	600	6,000	Box	12	3.7 x 5.6	2700
★ 20	70876	SKR420FLDWW Dimmable E26	100	950	8,000	Box	6	4.65 x 6.55	2700
15	70157	SKR315DWWD Dimmable E26 with disk	65	600	6,000	Box	12	3.7 x 5.6	2700

SPECIAL NOTES

>> All DimMax and DimMax Floods work with most incandescent dimmers

APPLICATIONS

- Table & floor lamps
- Hanging pendant
- Ceiling fixtures
- Track & recessed Lighting

LOCATIONS

- Residential
- Restaurant
- Retail
- Kitchen
- Hotel/Motel
- Office
- Restaurant

BENEFITS

- Continuous dimming down to 20%
- Air-gap, amalgam technology, heat sink, and higher temperature (130°C) rated components for greater heat tolerance
- Automatic shut-off function protects lamp
- Works with most incandescent dimming controls
- Long life - lasts up to 6,000 hours

SPECIFICATIONS

- End of Life Ballast >> Yes
- Ballast Type >> Electronic
- Starting Method >> Instant Start
- Input Line Voltage >> 120VAC
- Input Line Frequency >> 50/60HZ
- Mini. Starting Temp. >> 0°F
- Max. Operating Temp. >> 100°F
- Color Rendering Index >> 84

MAX11076-03-8

All specifications are subject to change without notice



This device complies with Part 18 of the FCC rules. If interference occurs move this product away from the device or plug into a different outlet. This product may cause interference to radio equipment and should not be installed near maritime safety communications equipment or other critical navigation or communication equipment operating between 0.45-30MHz.