

PRODUCT FOCUS

PARs & Rs

Compact Fluorescent Flood Lamp

**FOR >> RECESSED CANS & HIGH HATS
>> CEILING MOUNTED STRIP
LIGHTING**



SKR315FL★
SKR315FLDL
SKR315FLCW★



SKR423FL★
SKR423FLDL
SKR423FLCW



SKR3820FL★
SKR3820FLHGW
SKR3820FLHGCW



SKR3823FL★
SKR3823FLDL

★ ENERGY STAR® qualified



- Fits flush with standard recessed can fixtures
- Same size and shape as incandescent lamps
- Long life, 8,000 hours; saves up to 75% in energy costs
- Par lamps suitable for indoor/outdoor use
- Frosted glass on R20, R30, and R40 for softer lighting

PRODUCT FOCUS

PARs & Rs

Compact Fluorescent Flood Lamp



R LAMPS

SKR211FLWW
8,000 Hour
(7) 6762707011 (2)*

SKR315FLWW★ 8,000 Hour
(7) 6762733015 (5)*

SKR315FLCW★ 8,000 Hour
(7) 6762733031 (5)*

SKR423FLWW★ 8,000 Hour
(7) 6762733023 (0)*

SKR315FLDL
8,000 Hour
(7) 6762733019 (3)*

SKR423FLCW
8,000 Hour
(7) 6762733030 (8)*

SKR423FLDL★
8,000 Hour
(7) 6762711612 (4)*



PAR LAMPS

SKR2009FLWW★ 8,000 Hour
(7) 6762711197 (6)*

SKR3015FLWW 8,000 Hour
(7) 6762733010 (0)*

SKR3820FLWW★ 8,000 Hour
(7) 672733032 (2)*

SKR3823FLWW★ 8,000 Hour
(7) 6762733016 (2)*

SKR2009FLDL 8,000 Hour
(7) 6762711199 (0)*

SKR3015FLDL 8,000 Hour
(7) 6762733020 (9)*

SKR3820FLHGW★ 8,000 Hour
(7) 6762711563 (9)*

SKR3823FLDL 8,000 Hour
(7) 6762711150 (1)*

SKR3820FLHGCW★ 8,000 Hour
(7) 6762711599 (8)*

R LAMPSPECIFICATIONS

Watts	Order Code	Description	Incandescent Equivalent	Lumens	Lamp Life (Hrs)	Pack Type	Case Pack	Dimensions (W" x MOL")	K
11	07011	SKR211FLWW R20 FloodMax	40	400	8,000	Box	25	2.5 x 4.8	2700
★ 15	33015	SKR315FLWW R30 FloodMax	75	690	8,000	Box	12	3.75 x 5.6	2700
★ 15	33031	SKR315FLCW R30 FloodMax Cool White	75	690	8,000	Box	12	3.75 x 5.6	4100
15	33019	SKR315FLDL R30 FloodMax Daylight	75	690	8,000	Box	12	3.75 x 5.6	5000
★ 23	33023	SKR423FLWW R40 FloodMax	125	1300	8,000	Box	12	4.9 x 6.25	2700
23	33030	SKR423FLCW R40 FloodMax Cool White	125	1300	8,000	Box	12	4.9 x 6.25	4100
23	70282	SKR423FLDL R40 FloodMax Daylight	125	1300	8,000	Box	12	4.9 x 6.25	5000

PAR LAMPSPECIFICATIONS

Watts	Order Code	Description	Incandescent Equivalent	Lumens	Lamp Life (Hrs)	Pack Type	Case Pack	Dimensions (W" x MOL")	K
★ 9	11197	SKR2009FLWW Par20 Indoor/Outdoor	30	330	8,000	Box	12	2.45 x 3.8	2700
9	11199	SKR2009FLDL Par20 Indoor/Outdoor	30	330	8,000	Box	12	2.45 x 3.8	5000
15	33010	SKR3015FLWW Par30 Indoor/Outdoor	75	650	8,000	Box	12	3.75 x 5.1	2700
15	33020	SKR3015FLDL Par30 In-Outdoor Daylight	75	650	8,000	Box	12	3.75 x 5.1	5000
★ 20	33032	SKR3820FLWW Par38 Indoor/Outdoor	75	900	8,000	Box	12	4.8 x 5.5	2700
20	70226	SKR3820FLHGW Par38 Indoor/Outdoor	75	900	8,000	Box	12	4.8 x 5.5	2700
20	70272	SKR3820FLHGCW Par38 Indoor/Outdoor	75	900	8,000	Box	12	4.8 x 5.5	4100
★ 23	33016	SKR3823FLWW Par38 Indoor/Outdoor	100	1250	8,000	Box	12	5 x 6.2	2700
23	11150	SKR3823FLDL Par38 In-Outdoor Daylight	100	1250	8,000	Box	12	5 x 6.2	5000

MAX8741



FCC Certified
★ UPC Codes
★ ENERGY STAR®
Qualified

All specifications are subject to change without notice

PRODUCT FOCUS

PARs & Rs

Compact Fluorescent Flood Lamp



Perma Disk



SKR2009FL30PD
8,000 Hour
(7) 6762711382 (6)*



SKR3015FL30PD
8,000 Hour
(7) 6762733033 (9)*



SKR3823FL30PD
8,000 Hour
(7) 6762733034 (6)*

PAR LAMP PERMA DISK SPECIFICATIONS

Watts	Order Code	Description	Incandescent Equivalent	Lumens	Lamp Life (Hrs)	Pack Type	Case Pack	Dimensions (W" x MOL")	K
9	11382	SKR2009FL30PD Par20 with disk	30	350	8,000	Box	12	2.45 x 3.8	3000
15	33033	SKR3015FL30PD Par30 with disk	75	650	8,000	Box	12	3.75 x 5.1	3000
23	33034	SKR3823FL30PD Par38 with disk	100	1250	8,000	Box	12	5 x 6.2	3000

SPECIAL NOTES

>> Uses amalgam advanced technology for higher lumen maintenance and consistent color.

APPLICATIONS

- Recessed cans & high hats
- Ceiling mounted strip lighting
- Outdoor

LOCATIONS

- Residential/Office/Retail
- Hotel/Motel/Restaurant
- School/Hospital/Property Management

BENEFITS

- Same size and shape as incandescent lamps
- Fully flush with standard high hat or recessed can applications
- Par lamps suitable for indoor/ outdoor use
- Patented Air-Gap on 30/40 guarantees longer life in hot locations
- Frosted glass on R20/30/40 generates softer, natural lighting

SPECIFICATIONS

- Ballast Type >> Electronic
- Starting Method >> Instant Start
- Input Line Voltage >> 120VAC
- Input Line Frequency >> 50/60HZ
- Mini. Starting Temp. >> 0°F
- Max. Operating Temp. >> 100°F
- Color Rendering Index >> 84

MAX8741

All specifications are subject to change without notice



FCC Certified
★ UPC Codes
★ ENERGY STAR®
Qualified