

PRODUCT FOCUS **PARs & Rs**

Compact Fluorescent Flood Lamp



Perma Disk



SKR2009FL30PD
8,000 Hour
(7) 6762711382 (6)*



SKR3015FL30PD
8,000 Hour
(7) 6762733033 (9)*



SKR3823FL30PD★
8,000 Hour
(7) 6762733034 (6)*

R LAMP PERMA DISKSPECIFICATIONS

Watts	Order Code	Description	Incandescent Equivalent	Lumens	Lamp Life (Hrs)	Pack Type	Case Pack	Dimensions (W" x MOL")	K
15	34010	SKR315FLWWPD Par20 E26 with disk	75	750	8,000	Box	12	3.75 x 5.6	2700
23	33026	SKR423FLCWPDP Par30 E26 with disk	125	1100	10,000	Box	12	4.8 x 6.3	4100

PAR LAMP PERMA DISKSPECIFICATIONS

Watts	Order Code	Description	Incandescent Equivalent	Lumens	Lamp Life (Hrs)	Pack Type	Case Pack	Dimensions (W" x MOL")	K
9	11382	SKR2009FL30PD Par20 E26 with disk	30	350	8,000	Box	12	2.45 x 3.8	3000
15	33033	SKR3015FL30PD Par30 E26 with disk	75	750	8,000	Box	12	3.75 x 5.1	3000
★ 18	11189	SKR3818FLWWPD Par38 E26 with disk	100	1200	8,000	Box	12	5 x 6.2	2700
23	33034	SKR3823FL30PD Par38 E26 with disk	100	1200	8,000	Box	12	5 x 6.2	3000



SKR315FLDWW★
6,000 Hour
(7) 6762733011 (7)*



SKR315FLDWWPD★
6,000 Hour
(7) 6762711515 (8)*

DIMMAXSPECIFICATIONS

Watts	Order Code	Description	Incandescent Equivalent	Lumens	Lamp Life (Hrs)	Pack Type	Case Pack	Dimensions (W" x MOL")	K
★ 15	33011	SKR315FLDWW E26 Dimmable	65	600	6,000	Box	12	3.7 x 5.6	2700
15	70157	SKR315DWWPD E26 Dimmable with disk	65	600	6,000	Box	12	3.7 x 5.6	2700

PF greater than >.5

All of our PARs are parabolic aluminized reflector lamps



FCC Certified

★ UPC Codes

★ ENERGY STAR®

Qualified

SPECIAL NOTES	APPLICATIONS	LOCATIONS
>> Uses amalgam advanced technology for higher lumen maintenance and consistent color.	• Recessed cans & high hats • Ceiling mounted strip lighting • Outdoor	• Residential/Office/Retail • Hotel/Motel/Restaurant • School/Hospital/Property Management

BENEFITS	SPECIFICATIONS
• Same size and shape as incandescent lamps • Fully flush with standard high hat or recessed can applications • Par lamps suitable for indoor/ outdoor use • Patented Air-Gap on 30/40 guarantees longer life in hot locations • Frosted glass on R20/30/40 generates softer, natural lighting	• Ballast Type >> Electronic • Starting Method >> Instant Start • Input Line Voltage >> 120VAC • Input Line Frequency >> 50/60HZ • Mini. Starting Temp. >> 0°F • Max. Operating Temp. >> 100°F • Color Rendering Index >> 84

MAX11073-03-8

PF greater than >.5

All of our PARs are parabolic aluminized reflector lamps

All specifications are subject to change without notice



This device complies with Part 18 of the FCC rules. If interference occurs move this product away from the device or plug into a different outlet. This product may cause interference to radio equipment and should not be installed near maritime safety communications equipment or other critical navigation or communication equipment operating between 0.45-30MHz.



FCC Certified
★ UPC Codes
★ ENERGY STAR®
Qualified