

## T2 Spirals

### Compact Fluorescent Lamps

#### T2 Spiral SPECIFICATIONS



MLS9T2

SKS13T2

SKS18T2

SKS23T2

All specifications are subject to change without notice

| Order Code | Watts | Description                  | Incandescent Equivalent | Lumens | Lamps Life (Hrs) | Pack Type | Case Pack | Dimension (W" x MOL") | CCT   |
|------------|-------|------------------------------|-------------------------|--------|------------------|-----------|-----------|-----------------------|-------|
| 70378      | 9     | MLS9T2WW                     | 40                      | 550    | 10,000           | Box       | 48        | 1.7 x 3.6             | 2700K |
| 70553      | 9     | MLS9T2CW                     | 40                      | 550    | 10,000           | Box       | 48        | 1.6 x 4.40            | 4100K |
| 70545      | 9     | MLS9T2DL                     | 40                      | 550    | 10,000           | Box       | 48        | 1.7 x 3.6             | 5000K |
| 72344      | 13    | SKS13T2WW-110                | 60                      | 900    | 10,000           | Box       | 48        | 1.8 x 4.1             | 2700K |
| 76646      | 13    | SKS13T2WW-149                | 60                      | 900    | 10,000           | Box       | 50        | 1.9 x 3.6             | 2700K |
| 76666      | 13    | SKS13T2WW-149/BP (Bulk pack) | 60                      | 900    | 10,000           | Box       | 50        | 1.9 x 3.6             | 2700K |
| 76647      | 13    | SKS13T2CW-149                | 60                      | 900    | 10,000           | Box       | 50        | 1.9 x 3.6             | 4100K |
| 76462      | 18    | SKS18T2WW-149                | 75                      | 1200   | 10,000           | Box       | 50        | 2.4 x 4.25            | 2700K |
| 75486      | 18    | SKS18T2WW/4P-149 (4-pack)    | 75                      | 1200   | 10,000           | Box       | 36        | 2.4 x 4.25            | 2700K |
| 75507      | 18    | SKS18T2CW-149                | 75                      | 1200   | 10,000           | Box       | 50        | 2.4 x 4.25            | 4100K |
| 70842      | 23    | SKS23T2CW                    | 100                     | 1600   | 10,000           | Box       | 48        | 2.1 x 4.9             | 4100K |
| 70843      | 23    | SKS23T2DL                    | 100                     | 1600   | 10,000           | Box       | 48        | 2.1 x 4.9             | 5000K |
| 76464      | 23    | SKS23T2WW-149                | 100                     | 1600   | 10,000           | Box       | 50        | 2.0 x 4.25            | 2700K |
| 76465      | 23    | SKS23T2CW-149                | 100                     | 1600   | 10,000           | Box       | 50        | 2.0 x 4.25            | 4100K |
| 76466      | 23    | SKS23T2DL-149                | 100                     | 1600   | 10,000           | Box       | 50        | 2.0 x 4.25            | 5000K |

#### SPECIAL NOTES

- >> Do not use on circuits with dimmers, timers or other control devices
- >> Not for use in totally enclosed fixtures

#### APPLICATIONS

- Table & Floor Lamps
- Recessed Light
- Corridor Light & Wall Sconce

#### LOCATIONS

- Residential
- Restaurant
- Retail
- Office
- School/Hospital
- Hotel/Motel

#### BENEFITS

- Ultra mini size fits most fixtures
- Long life – lasts up to 10,000 hours
- Saves Energy – up to 75% savings
- Instant-on, flicker-free electronics

#### SPECIFICATIONS

- Ballast Type >> Electronic
- Starting Method >> Instant Start
- Input Line Voltage >> 120VAC
- Input Line Frequency >> 50/60HZ
- Min. Starting Temp. >> 0°F
- Max. Operating Temp. >> 100°F
- Color Rendering Index >> 82

MAX11197



This device complies with Part 18 of the FCC rules. If interference occurs move this product away from the device or plug into a different outlet. This product may cause interference to radio equipment and should not be installed near maritime safety communications equipment or other critical navigation or communication equipment operating between 0.45-30MHz.