

HIGH LUMEN SPIRALS

Compact Fluorescent Lamp

FOR >> TABLE & FLOOR LAMPS
>> RECESSED LIGHT
>> CORRIDOR LIGHT
>> WALL SCNCE



SKS15EAHLWWBP

10,000 Hour
(7) 6762711709 (1) ⚡

MLM23SHLWWBP

10,000 Hour
(7) 6762711710 (7) ⚡

SKS15EAHLWWWB

10,000 Hour
(7) 6762711643 (8) ⚡

MLM23SHLWWWB

10,000 Hour
(7) 6762711644 (5) ⚡

SKS15EAHLWWEG

10,000 Hour
(7) 6762711721 (3) ⚡

MLM23SHLWWEG

10,000 Hour
(7) 6762711722 (0) ⚡

HIGH LUMEN SPECIFICATIONS

Watts	Order Code	Description	Incandescent Equivalent	Lumens	Lamp Life (Hrs)	Pack Type	Case Pack	Dimensions (W" x MOL")	K
★ 15	70399	SKS15EAHLWWBP Color Box	75	1100	10,000	Box	48	1.6 x 4.4	2700
★ 15	70334	SKS15EAHLWWWB White Box	75	1100	10,000	Box	48	1.6 x 4.4	2700
★ 15	70411	SKS15EAHLWWEG Egg Crate	75	1100	10,000	Box	50	1.6 x 4.4	2700
★ 23	70380	MLM23SHLWWBP Colo Box	100	1650	10,000	Box	48	2.3 x 4.6	2700
★ 23	70381	MLM23SHLWWWB White Box	100	1650	10,000	Box	48	2.3 x 4.6	2700
★ 23	70412	MLM23SHLWWEG Egg Crate	100	1650	10,000	Box	50	2.3 x 4.6	2700

SPECIAL NOTES

- >> Do not use on circuits with dimmers, timers or other control devices
- >> Not for use in totally enclosed fixtures

APPLICATIONS

- Table & Floor Lamps
- Recessed Light
- Corridor Light & Wall Sconce

LOCATIONS

- Residential
- Office
- Restaurant
- School/Hospital
- Retail
- Hotel/Motel

BENEFITS

- Ultra mini size fits most fixtures
- Long life – lasts up to 10,000 hours
- Saves Energy – up to 75% savings
- Instant-on, flicker-free electronics

SPECIFICATIONS

- Ballast Type >> Electronic
- Starting Method >> Instant Start
- Input Line Voltage >> 120VAC
- Input Line Frequency >> 50/60HZ
- Mini. Starting Temp. >> 0°F
- Max. Operating Temp. >> 100°F
- Color Rendering Index >> 84

MAX8553

All specifications are subject to change without notice



FCC Certified
★ UPC Codes
★ ENERGY STAR®
Qualified