



POLE OFFERING



PART #	MOUNTING HT	MAX EPA				SHAFT DIAMETER	WALL THICKNESS (ga)	ANCHOR BOLT DIA	BOLT CIRCLE	PRODUCT(S)			
		(80)	(90)	(100)	(120)								
ROUND STRAIGHT ANCHOR BASE													
SL-RSP-8-3-11-AB-XX-YY	8 FT	11.2	8.4	6.2	3.7	3.0"	11	0.75"	8.5"	■ ●			
SL-RSP-10-3-11-AB-XX-YY	10 FT	9.0	6.7	5.0	3.0					■ ●			
SL-RSP-12-3-11-AB-XX-YY	12 FT	6.9	5.0	3.9	2.1					■ ● ▲			
SL-RSP-14-3-11-AB-XX-YY	14 FT	5.5	3.9	2.9	1.4					▲			
SL-RSP-14-4-11-AB-XX-YY		11.7	8.9	7.1	4.0					▲ ✱			
SL-RSP-16-4-11-AB-XX-YY	16 FT	9.0	6.8	5.3	2.9					▲			
SL-RSP-18-4-11-AB-XX-YY	18 FT	7.1	5.2	4.0	2.2								
SL-RSP-20-4-11-AB-XX-YY	20 FT	5.6	4.1	3.1	1.7								
SL-RSP-25-5-11-AB-XX-YY	25 FT	6.7	5.0	3.7	2.0								
SL-RSP-25-5-7-AB-XX-YY		12.0	9.2	7.5	4.2					▲ ✱			
SL-RSP-30-5-11-AB-XX-YY	30 FT	4.0	2.8	2.0	N/A					7	1.00"	10.0"	
SL-RSP-30-5-7-AB-XX-YY		7.9	6.6	4.8	2.7					11	0.75"	8.5"	
										7	1.00"	10.0"	

PART #	MOUNTING HT	MAX EPA				SHAFT DIAMETER	WALL THICKNESS (ga)	ANCHOR BOLT DIA	BOLT CIRCLE	PRODUCT(S)				
		(80)	(90)	(100)	(120)									
SQUARE STRAIGHT ANCHOR BASE														
SL-RPSQ-10-4-11-AB-XX-YY	10 FT	25.7	20.8	16.8	11.8	4.0"	11	0.75"	8.5"	■ ●				
SL-RPSQ-12-4-11-AB-XX-YY	12 FT	20.5	16.6	13.4	9.4					■ ● ▲				
SL-RPSQ-14-4-11-AB-XX-YY	14 FT	16.6	13.5	10.9	7.7									
SL-RPSQ-15-4-11-AB-XX-YY	15 FT	15.1	12.3	9.8	7.0					■ ● ▲ ▲ ✱				
SL-RPSQ-16-4-11-AB-XX-YY	16 FT	13.6	11.0	8.9	6.3									
SL-RPSQ-18-4-11-AB-XX-YY	18 FT	11.1	9.0	7.2	5.1									
SL-RPSQ-20-4-11-AB-XX-YY	20 FT	9.0	7.3	5.9	4.2									
SL-RPSQ-20-4-7-AB-XX-YY		15.9	12.5	10.1	7.1					▲ ✱				
SL-RPSQ-20-5-11-AB-XX-YY	20 FT	16.0	12.9	10.4	7.4					5.0"	11	1.00"	11.0"	✱
SL-RPSQ-20-5-7-AB-XX-YY		26.4	21.3	17.2	12.1					7	1.00"	11.0"	✱	
SL-RPSQ-25-4-11-AB-XX-YY	25 FT	4.1	3.3	2.6	1.8					4.0"	11	0.75"	8.5"	
SL-RPSQ-25-4-7-AB-XX-YY		9.7	7.8	6.3	4.5					7	0.75"	8.5"		
SL-RPSQ-25-5-11-AB-XX-YY		8.5	6.9	5.6	4.0					11	5.0"	11.0"		
SL-RPSQ-25-5-7-AB-XX-YY	25 FT	17.5	14.2	11.4	8.1					5.0"	7	1.00"	11.0"	▲ ✱ ✱
SL-RPSQ-25-6-7-AB-XX-YY		27.5	22.3	18.0	12.6					6.0"	7	1.00"	11.5"	✱ ✱
SL-RPSQ-30-5-11-AB-XX-YY	30 FT	4.2	3.4	2.7	1.9					5.0"	11	0.75"	11.0"	
SL-RPSQ-30-5-7-AB-XX-YY		10.6	8.6	6.9	4.9					7	1.00"	11.0"		
SL-RPSQ-30-6-7-AB-XX-YY		17.9	14.5	11.7	8.3					6.0"	7	1.00"	11.5"	✱ ✱ ✱

XX = MOUNTING OPTION, T2 = 2 3/8" TENON, T2.5 = 2 7/8" TENON, T3 = 3" TENON YY = FINISH COLOR, BK = BLACK, DB = DARK BRONZE, GR = GRAY

PART #	MOUNTING HT	TOTAL HT	MAX EPA				SHAFT DIAMETER	WALL THICKNESS (ga)	PRODUCT(S)	
			(80)	(90)	(100)	(120)				
ROUND STRAIGHT DIRECT BURIAL										
SL-RSP-8-3-11-EMB-XX-YY	8 FT	11 FT	11.2	8.4	6.2	3.7	3.0"	11	■ ●	
SL-RSP-10-4-11-EMB-XX-YY	10 FT	13 FT	9.0	6.7	5.0	3.0	4.0"		■ ●	
SL-RSP-12-4-11-EMB-XX-YY	12 FT	15 FT	6.9	5.0	3.9	2.1	4.0"		■ ● ▲	
SL-RSP-14-4-11-EMB-XX-YY	14 FT	18 FT	11.7	8.9	7.1	4.0	4.0"		▲ ▲ ✱	
SL-RSP-16-4-11-EMB-XX-YY	16 FT	20 FT	9.0	6.8	5.3	2.9	4.0"		▲	
SL-RSP-18-5-11-EMB-XX-YY	18 FT	22 FT	7.1	5.2	4.0	2.2	5.0"			
SL-RSP-20-5-7-EMB-XX-YY	20 FT	24 FT	16.4	12.6	10.0	6.6	5.0"		7	▲ ✱ ✱
SL-RSP-20-5-11-EMB-XX-YY			9.0	7.3	5.9	4.2	11			
SL-RSP-25-5-11-EMB-XX-YY	25 FT	30 FT	6.7	5.0	3.7	2.0	5.0"		11	
SL-RSP-25-5-7-EMB-XX-YY			12.0	9.2	7.5	4.2	7		▲ ✱	

PART #	MOUNTING HT	TOTAL HT	MAX EPA				SHAFT DIAMETER	WALL THICKNESS (ga)	PRODUCT(S)		
			(80)	(90)	(100)	(120)					
SQUARE STRAIGHT DIRECT BURIAL											
SL-RPSQ-10-4-11-EMB-XX-YY	10 FT	13 FT	25.7	20.8	16.8	11.8	4.0"	11	■ ●		
SL-RPSQ-12-4-11-EMB-XX-YY	12 FT	15 FT	20.5	16.6	13.4	9.4			4.0"	11	■ ● ▲
SL-RPSQ-14-4-11-EMB-XX-YY	14 FT	18 FT	16.6	13.5	10.9	7.7			4.0"	11	■ ● ▲ ▲ ✱
SL-RPSQ-15-4-11-EMB-XX-YY	15 FT	19 FT	15.1	12.3	9.8	7.0			4.0"	11	
SL-RPSQ-16-4-11-EMB-XX-YY	16 FT	20 FT	13.6	11.0	8.9	6.3			4.0"	11	
SL-RPSQ-18-4-11-EMB-XX-YY	18 FT	22 FT	11.1	9.0	7.2	5.1			4.0"	11	
SL-RPSQ-20-4-11-EMB-XX-YY	20 FT	24 FT	9.0	7.3	5.9	4.2			5.0"	11	
SL-RPSQ-20-4-7-EMB-XX-YY			15.9	12.5	10.1	7.1			7	▲ ✱	
SL-RPSQ-20-5-11-EMB-XX-YY	20 FT	24 FT	16.0	12.9	10.4	7.4			5.0"	11	✱
SL-RPSQ-20-5-7-EMB-XX-YY			26.4	21.3	17.2	12.1			7	✱ ✱	
SL-RPSQ-25-5-11-EMB-XX-YY	25 FT	30 FT	8.5	6.9	5.6	4.0			5.0"	11	
SL-RPSQ-25-5-7-EMB-XX-YY			17.5	14.2	11.4	8.1			7	▲ ✱ ✱	
SL-RPSQ-25-6-7-EMB-XX-YY	25 FT	30 FT	27.5	22.3	18.0	12.6			6.0"	7	✱ ✱
SL-RPSQ-30-5-7-EMB-XX-YY			10.6	8.6	6.9	4.9			5.0"	7	
SL-RPSQ-30-6-7-EMB-XX-YY	30 FT	35 FT	17.9	11.7	8.3	8.3			6.0"	7	✱ ✱ ✱

XX = MOUNTING OPTION, T2 = 2 3/8" TENON, T2.5 = 2 7/8" YY = FINISH COLOR, BK = BLACK, DB = DARK BRONZE, GR = GRAY

- OFF-GRID POST TOP LIGHT (SL-SPT)
- ▲ OFF-GRID AREA LIGHT (RP-SAL-8W)
- ✱ OFF-GRID AREA LIGHT (SL-SAL-60L)
- ✱ INTELLIGENT MODULAR AREA LIGHT (SL-MA1/SL-MA2)
- OFF-GRID PATHWAY LIGHT (SL-CPT)
- ▲ OFF-GRID AREA LIGHT (RP-SAL-30W)
- ✱ OFF-GRID AREA LIGHT (SL-SAL-100L)
- ✱ INTELLIGENT MODULAR DECORATIVE LIGHT (SL-MD1)