

PART #	MOUNTING HT	TOTAL HT	MAX EPA				SHAFT DIAMETER	WALL THICKNESS (ga)	PRODUCT(S)
			(80)	(90)	(100)	(120)			
ROUND STRAIGHT DIRECT BURIAL									
SL-RSP-8-3-11-EMB-XX-YY	8 FT	11 FT	11.2	8.4	6.2	3.7	3.0"	11	■ ●
SL-RSP-10-4-11-EMB-XX-YY	10 FT	13 FT	9.0	6.7	5.0	3.0	4.0"		■ ●
SL-RSP-12-4-11-EMB-XX-YY	12 FT	15 FT	6.9	5.0	3.9	2.1			■ ● ▲
SL-RSP-14-4-11-EMB-XX-YY	14 FT	18 FT	11.7	8.9	7.1	4.0			▲ ▲ ✱
SL-RSP-16-4-11-EMB-XX-YY	16 FT	20 FT	9.0	6.8	5.3	2.9			▲
SL-RSP-18-5-11-EMB-XX-YY	18 FT	22 FT	7.1	5.2	4.0	2.2	5.0"		
SL-RSP-20-5-7-EMB-XX-YY	20 FT	24 FT	16.4	12.6	10.0	6.6		7	▲ ✱ ✱
SL-RSP-20-5-11-EMB-XX-YY			9.0	7.3	5.9	4.2		11	
SL-RSP-25-5-11-EMB-XX-YY	25 FT	30 FT	6.7	5.0	3.7	2.0			
SL-RSP-25-5-7-EMB-XX-YY			12.0	9.2	7.5	4.2	7	▲ ✱	

XX = MOUNTING OPTION, T2 = 2 3/8" TENON, T2.5 = 2 7/8" (POLE CAP INCLUDED AS STANDARD. TENON TOP OPTIONAL — SPECIFY TENON SIZE ONLY WHEN ORDERING A TENON)
 YY = FINISH COLOR, BK = BLACK, DB = DARK BRONZE, GR = GRAY

- OFF-GRID POST TOP LIGHT (SL-SPT)
- ▲ OFF-GRID AREA LIGHT (RP-SAL-8W)
- ✱ OFF-GRID AREA LIGHT (SL-SAL-60L)
- + INTELLIGENT MODULAR AREA LIGHT (SL-MA1/SL-MA2)
- OFF-GRID PATHWAY LIGHT (SL-CPT)
- ▲ OFF-GRID AREA LIGHT (RP-SAL-30W)
- ✱ OFF-GRID AREA LIGHT (SL-SAL-100L)
- + INTELLIGENT MODULAR DECORATIVE LIGHT (SL-MD1)