

Miniature E10 Screw Base

Direct Incandescent Replacement
Up to 90% Energy Savings - Long Life - No Heat

4

E10 Miniature Base - T3¼ (9mm), Single-Chip

Series: SF321

Replaces Incandescent: 5/6V; 407, 502, 3708 12/14V; 3724, 1446 24V; 1449, 52

Std. Voltages: 6VDC, 12/14VDC, 24/28VDC, 6VAC, 120VAC

Polarity: Bipolar DC (+/-)

Dimensions: Ø9.91 x 26mm

Colors: Warm White ● Cool White ● Red ● Yellow ● Green ●



E10 Miniature Base - T3¼, 6 Cluster

Series: SSF3126

Replaces Incandescent: 1446, 1447, 1449, 1487, 50

Std. Voltages: 8VDC, 14VDC, 18VDC

Polarity: Bipolar DC (+/-)

Dimensions: Ø10.36 x 23.88mm

Color: Warm White ●



Candelabra E12 Screw Base

Direct Incandescent Replacement
Up to 90% Energy Savings - Long Life - No Heat

Candelabra E12 - S6, 4 Cluster, Short Body

Series: SF464

Replaces Incandescent: Low-Wattage Nightlights, Industrial Indicators, Pilot Lights

Std. Voltages: 24 VDC, 120 VAC

Polarity: Bipolar DC (+/-)

Dimensions: 0.46" (11.68mm) Base OD, 1.35" (34.3mm) MOL

Colors: Warm White ● Cool White ● Red ● Green ●



Candelabra E12 - S6, 4 Cluster, Long Body

Series: SLF464

Replaces Incandescent: Low-Wattage Nightlights, Industrial Indicators, Pilot Lights

Std. Voltages: 24VDC, 120VAC, 130VDC

Polarity: Bipolar DC (+/-)

Dimensions: 0.46" (11.7mm) Base OD, 1.88" (47.8mm) MOL

Colors: Warm White ● Cool White ● Red ● Green ●



Candelabra E12 - S6, 6/7 Cluster, Long Body

Series: SLF467

Replaces Incandescent: Low-Wattage Nightlights, Industrial Indicators, Pilot Lights

Std. Voltages: 24VDC, 120VAC, 130VDC

Polarity: Bipolar DC (+/-)

Dimensions: 0.46" (11.7mm) Base OD, 1.88" (47.8mm) MOL

Colors: Warm White ● Cool White ● Red ● Yellow ● Green ●



Candelabra E12 - S6, 7 Cluster, Long Body, UL Listed

Series: SLF467-UL

Replaces Incandescent: Low-Wattage Nightlights, Industrial Indicators, Pilot Lights

Std. Voltages: 120VAC

Dimensions: 0.46" (11.7mm) Base OD, 1.88" (47.8mm) MOL

Colors: Warm White ●

