

# 24S1100 W Power Supply

Damp/Dry-rated 100 Watt power supply

- Universal input voltage – 100-277 VAC, 50-60 Hz input
- Constant voltage output at 24 V and 96 W
- Auto-resetting – No fuses to replace or circuit breaker to reset – Short circuit protection automatically resets when short condition is corrected
- Simple secondary hook-ups – No minimum load or load balancing required
- Rugged and compact



## Specifications

|                                    |                                                         |
|------------------------------------|---------------------------------------------------------|
| <b>Part number</b> .....           | 701895-24S1                                             |
| <b>Dimensions L × W × H</b> .....  | 7.60 in × 2.48 in × 1.59 in<br>(193 mm × 63 mm × 40 mm) |
| <b>Nominal input voltage</b> ..... | 100-277 VAC, 50-60 Hz                                   |
| <b>Maximum input current</b> ..... | 1.4 A                                                   |
| <b>Power output</b> .....          | 96 W @ 24 VDC, Class 2 output<br>(North America only)   |
| <b>Location rating</b> .....       | Damp and dry locations                                  |
| <b>Operating temperature</b> ..... | -40° C to +60° C                                        |
| <b>Weight</b> .....                | 1.9 lbs (0.86 kg)                                       |
| <b>Compatibility</b> .....         | SloanLED 24 VDC products                                |



**SloanLED Headquarters**  
805.676.3200 • [info@SloanLED.com](mailto:info@SloanLED.com)

**SloanLED Europe b.v.**  
+31 88 12 44 900 • [Europe@SloanLED.com](mailto:Europe@SloanLED.com)



[SloanLED.com](http://SloanLED.com)

© 2018 SloanLED Rev A 2018-12-21

Specifications subject to change without notice.

 **SloanLED®**  
Leaders in LED Technology