


SignBOX II

LED illumination for single or double-sided sign boxes

Specifications

Part number	Single-sided.....6500 K	701946-6WS201
	Single-sided.....5000 K	701946-5WS201
	Double-sided6500 K	701946-6WD201
	Double-sided5000 K	701946-5WD201
Dimensions L × W × H	216 mm × 26 mm × 8 mm	
	(8.5 in × 1.0 in × 0.3 in)	
	60 modules per 6.1 m (20 ft) chain	
Viewing angle	120°	
LEDs per module	Single-sided.....3	
	Double-sided.....6	
Modules per meter (foot)	10 (3)	
Coverage per row	300 mm (12 in)	
Optimal light throw	125 - 300 mm (5 - 12 in) from face	
Operating temperature	-40° C to +70° C	
Protection class	IP66	
Life rating	>60,000 hours	
Special feature	Cuttable in 100 mm (4 in) increments	
Power per module	Single-sided.....0.90 W	
	Double-sided1.80 W	
Efficacy	117 lm/W	
Fastening	Clamps with mechanical fasteners	
Packaging	60 modules per carton, 8 clamps included	
Color temperatures	6500 K, 5000 K	
Lumens per module	Single-sided.....105	
	Double-sided210	
Mounting hardware	Bracket.....Bag of 10	401309-10
	Clamp.....Bag of 16	410155-16
	Coupler	401330-10
	Bag of 10	



Power Supply Capacity

12 VDC Power supply*	Maximum modules single-sided or one leg of double-sided	Maximum modules double-sided, both legs
20 W Power Supply	20	10
25 W Power Supply (EU/ROW ONLY)	25	12
30 W Power Supply (EU/ROW ONLY)	30	15
60 W Power Supply	60	30
2 × 60 W Power Supply	60 × 2	30 × 2
2 × 75 W Power Supply (EU/ROW ONLY)	75 × 2	37 × 2
Power used per m (ft) in watts	8.9W (2.7)	17.7W (5.4)

* Configured for Class 2 Output.

NOTE: When mixing modules of different sizes/colors or various products on the same power supply, simply add all the power requirements for the respective footages of each product. Then choose appropriate power supplies to provide adequate power output. The actual number of power supplies needed may vary based on how the materials are distributed across the project.

Accessories



Clamp

410155-16

Each carton of SignBOX II comes with 8 clamps



Bracket

401309-10

Optional –
Sold in bags of 10.



Coupler

401330-10

Optional –
Sold in bags of 10.



SignBOX™ II is covered by US and foreign patents pending.

SignBOX II

LED illumination for single or double-sided sign boxes

Density Guidelines

Model	Module color	Cabinet Depth	mm/inches on center	Watts per module
SignBOX II Single-sided	5000 K / 6500 K	127-305 mm (5-12")	305 mm / 12"	0.90 W
SignBOX II Double-sided	5000 K / 6500 K	254-610 mm (10-24")	305 mm / 12"	1.80 W

Notes:

- 1) All SignBOX II products have 10 modules per meter. Optimal mounting position for illumination is 203 mm from the face.
- 2) To minimize the potential for shadows/hot spots in applications when using frame support tubes/poles; mount modules or frame support tubes such that the tubes are centered in between modules and at a depth that will not directly interfere with the beam angle of the LEDs.
Use SignComp Adjustable Frame Brace (P/N: 5357) or equivalent.
- 3) It is recommended that you first test the LED density in a sample cabinet to evaluate brightness, uniformity, and color.
- 4) Should you have questions or require assistance in testing, please contact your SloanLED customer service representative.
- 5) Products can be used in can depths deeper or shallower than listed above, but testing is recommended.
- 6) The acrylic material used for all testing was 4.8 mm (3/16") thickness sign grade 2447 acrylic.

These guidelines are intended to provide only an approximation of SignBOX II product required for your cabinet, assuming an optimal balance of performance and cost. SloanLED is not responsible for the actual results based on the use of these guidelines.

SloanLED Headquarters

5725 Olivas Park Drive, Ventura, CA, USA
805.676.3200 • info@SloanLED.com

SloanLED Europe b.v.

Argonstraat 110, 2718 SN Zoetermeer, NL
+31 88 12 44 900 • europe@SloanLED.com



SloanLED.com

© 2022 SloanLED Rev D 2022-01-17

Specifications subject to change without notice.

