

# SlimLINER

Low-profile outdoor and indoor linear lighting

## Specifications

<b>Part number</b> .....	5000 K.....	701956-5WL461
	3500 K.....	701956-3WL461
<b>Dimensions L × W × H</b> .....	1168 mm × 23 mm × 9 mm	
<b>Lumens per fixture</b> .....	5000 K.....	970
	3500 K.....	825
<b>In-field bends</b> .....	Radial bend.....	305 mm
<b>Color temperatures (nominal)</b> ..	5000 K, 3500 K	
<b>Color rendering index (CRI)</b> .....	5000 K.....	70 (nominal)
	3500 K.....	82 (nominal)
<b>Estimated product lifetime</b> .....	50,000 hours (L <sub>70</sub> )	
<b>Operating temperature</b> .....	-40° C to 70° C	
<b>Protection class</b> .....	IP66 & IP68*	
<b>Special feature</b> .....	Cuttable every 150 mm for two usable sides	
<b>Power</b> .....	7.4 W per meter, 9.0 W per fixture	
<b>Efficacy</b> .....	5000 K.....	108 lm/W
	3500 K.....	92 lm/W
<b>Fastening</b> .....	Peel-n-stick or mounting clips (401203), 4 included with each unit	
<b>Power capacity</b> .....	6 units per SloanLED 60 W 12 VDC power supply	





\* IP66 & IP68 ratings provide protection for extreme outdoor and wet applications or harsh weather exposure. Do not mount in a submerged application.

## Power Supply Capacity

12 VDC Power supply†	Power output	SlimLINER Fixtures
20 W	20 W	2
25 W	25 W	2
60 W	60 W	6
120D1 120 W [701507-120D1]	120 W	6 × 2
Power used per meter in Watts		7.4 W per fixture


† Configured for Class 2 Output.

## Accessories



### Mounting Clip

401203  
Four (4) included with each unit.  
Sold in bags of 20.



**SloanLED Headquarters**  
3490 Venture Dr., San Angelo, TX, USA  
325 227 4577 • info@SloanLED.com

**SloanLED Europe b.v.**  
Argonstraat 110, 2718 SN Zoetermeer, NL  
+31 88 12 44 900 • europe@SloanLED.com



SloanLED.com

© 2024 SloanLED Rev D 2024-12-04

Specifications subject to change without notice.

**SloanLED**<sup>®</sup>  
A Principal Industries Company