



## Description

The small size of Venture's LED Linear Strip makes it an ideal choice for size commercial, industrial, retail and residential applications. Fixtures can be used in storage/utility areas, coves, display cases, shops, task and general area lighting.

## Construction

The fixture is powder coated for superior corrosion resistance. These versatile damp and dry rated fixtures are supplied with a low glare diffuse lens. Knock-out locations are available on both sides of the fixture as well as on top of the fixture as well.

## Electrical

Fixtures are provided with 120-277V 50/60 Hz drivers with 0-10V DC dimming as a standard.

## Mounting

Fixtures are for surface mounting applications. Can be pendant and suspended mounting as well. The lightweight design allows for easy installation/replacement of existing fixtures.

DLC Model# SM2-40N4A-BF1

## Product Performance

Wattage	40W
Lumen Output	4200
Correlated Color Temperature (CCT)	4000K
Color Rendering Index (CRI)	80
Life Hours	50,000
Operating Temperature Range	-4°F to 122°F (-20°C to 50°C)
Replaces Existing Fixture	80W T12 Fluorescent

## Physical Characteristics

Fixture Color	White
Width	3.35"
Length	48.0"
Height	3.56"

## Electrical Characteristics

Amperage Draw (Input Volts/Amps)	120/0.35 208/0.2 240/0.18 277/0.16
----------------------------------	------------------------------------

## Regulatory Qualifications

cULus Listed

DLC Model# SM2-40NA4-BF1

Suitable for Dry and Damp Locations

## Accessories

PH41623 - Motion only control sensor

PH77409 - Motion/Photocell/Dim control sensor



# Venture 4ft. LED Linear Strip

