

LUNERA HID LED LAMP

LED Replacement for High Intensity Discharge Lamps

[20,000lm / 15,000lm / 9,000lm / 4,500lm]

Mogul Base - Vertical Mount - Ballast Driven



Description

The Lunera HID LED lamp is a Ballast Driven (plug-and-play) LED replacement for Metal Halide (MH) and High Pressure Sodium (HPS) lamps with an E39 mogul base. This lamp replaces 400W~175W wattages of MH and HPS lamps in lighting applications such as High Bay, Low Bay, Parking Garages.

Lunera HID LED lamps feature a significantly lower energy consumption than conventional (High Intensity Discharge) HID lamps. These lamps deliver over 60% energy savings and have a rated life of 50,000 hours – 3 times longer than that of HID lamps.

Lunera's BallastLED technology makes these lamps truly plug-and-play by allowing them to operate directly off of existing magnetic HID ballasts.

The Lunera HID LED lamp is available in a range of color temperatures including 3500K, 4000K and 5000K. It delivers consistent light levels across its long life, which results in a high quality lighting experience for the building's occupants.



Features

- Replaces 400W ~ 175W High Intensity Discharge (MH and HPS) lamps
- Ballast-Driven plug-and-play installation; with existing magnetic HID ballast
- Works well in enclosed fixtures
- Up to 20,000, 15,000, 10,000 and 5,000 lumens fixture delivered light output
- Yields 60%-80% energy savings
- >80 CRI
- CCT 3500K, 4000K and 5000K
- Supports E39/EX39 Mogul base HID sockets
- Thermal IQ to support ambient temperatures up to 150°F



Ordering Information

Example: SN-V-E39-B-20KLM-840-G3

Series	Version	Socket Type	Power Supply	Lamp Lumens	CCT	Generation
SN: Lunera HID LED	V: Vertical Base [20KLM and 15KLM]	E39: Fits in mogul-base (E39/EX39) HID socket	B: Plug-and-Play Magnetic HID Ballast	20KLM: 20,000lm 15KLM: 15,000lm 9KLM: 9,000lm 4.5KLM: 4,500lm	835: 80CRI / 3500K 840: 80CRI / 4000K 850: 80CRI / 5000K	G3: 3rd Generation
SNSA: Lunera HID LED Sensor Lamp	VS: Vertical Short Base [9KLM and 4.5KLM]					

PROJECT	CONTACT	MODEL NO.
REFERENCE NO.	QUANTITY	DATE

For Technical Support:

www.lunera.com

T (650) 241-3874

1 of 5

<https://lunera.com/freshdesk.com/support/home>

Performance Specifications - Vertical Mount Lamp - 20,000lm / 15,000lm

	20,000 lumens	15,000 lumens
Illumination		
Color Temperatures	3500K, 4000K, 5000K	3500K, 4000K, 5000K
Lumens	Up to 20,000lm	Up to 15,000lm
Color Consistency	Lunera TruColor proprietary process	Lunera TruColor proprietary process
Lumen Maintenance (L70)	50,000+ hours life	50,000+ hours life
Electrical System		
Input Voltage	Dependent of HID ballast CWA Ballast Input (480V ~ 120V) HX Ballast Input (277V ~ 120V)	Dependent of HID ballast CWA Ballast Input (480V ~ 120V) HX Ballast Input (277V ~ 120V)
Average Lamp Power	230W	164W
Lamp Wattage Replaced	400W/320W/310W/250W	400W/320W/310W/250W
Physical		
Dimensions (H x W)	9.88" x 6.31"	9.88" x 6.31"
Weight	2.75lb	2.75lb
Housing and Finish	Painted	Painted
Heat Sink Size	6"	6"
Configuration	Vertical Standard Base/Heatsink (V)	Vertical Standard Base/Heatsink (V)
Lens	Clear	Clear
Environment		
Ambient Temperature	-40°F to 150°F*	-40°F to 150°F*
Humidity Rating	Damp OK, no direct water spray	Damp OK, no direct water spray
Fixture Type	Open or enclosed	Open or enclosed
Installation		
Socket Type	Fits vertical mount mogul base (E39/EX39) HID socket	Fits vertical mount mogul base (E39/EX39) HID socket
Certifications & Qualifications		
UL	Classified / Recognized US, CAN	Classified / Recognized US, CAN
RoHS Compliant	Contains no lead or mercury	Contains no lead or mercury
LM79, LM80, IES Files	Available	Available
DesignLights Consortium	DLC category not available	DLC category not available
Warranty		
Warranty	5 years	5 years

*Thermal IQ is a proprietary Lunera technology which enables the Susan Lamp to operate reliably up to 150°F ambient by dimming itself at extreme temperatures based upon thermal characteristics of the fixture in which it has been installed.

* Lamp dimming profiles subject to ballast type and environmental conditions. Contact Lunera for more detailed information.

Performance Specifications - Vertical Mount Lamp - 9,000lm / 4,500lm

	9,000 lumens	4,500 lumens
Illumination		
Color Temperatures	3500K, 4000K, 5000K	3500K, 4000K, 5000K
Lumens	Up to 9,000lm	Up to 4,500lm
Color Consistency	Lunera TruColor proprietary process	Lunera TruColor proprietary process
Lumen Maintenance (L70)	50,000+ hours life	50,000+ hours life
Electrical System		
Input Voltage	Dependent of HID ballast CWA Ballast Input (480V ~ 120V) HX Ballast Input (277V ~ 120V)	Dependent of HID ballast CWA Ballast Input (480V ~ 120V) HX Ballast Input (277V ~ 120V)
Average Lamp Power	103W	58W
Lamp Wattage Replaced	250W/175W/150W/100W/70W	175W/150W/100W/70W
Physical		
Dimensions (H x W)	8.59" x 6.31"	8.59" x 6.31"
Weight	1.9lb	1.9lb
Housing and Finish	Painted	Painted
Heat Sink Size	6" Small	6" Small
Configuration	Vertical Short Base/Heatsink (VS)	Vertical Short Base/Heatsink (VS)
Lens	Frosted or Type V Option	Frosted or Type V Option
Environment		
Ambient Temperature	-40°F to 150°F*	-40°F to 150°F*
Humidity Rating	Damp OK, no direct water spray	Damp OK, no direct water spray
Fixture Type	Open or enclosed	Open or enclosed
Installation		
Socket Type	Fits vertical mount mogul base (E39/EX39) HID socket	Fits vertical mount mogul base (E39/EX39) HID socket
Certifications & Qualifications		
UL	UL Classified & Recognized	UL Classified & Recognized
RoHS Compliant	Contains no lead or mercury	Contains no lead or mercury
LM79, LM80, IES Files	Available	Available
DesignLights Consortium	DLC category not available	DLC category not available
Warranty		
Warranty	5 years	5 years


*Thermal IQ is a proprietary Lunera technology which enables the Susan Lamp to operate reliably up to 150°F ambient by dimming itself at extreme temperatures based upon thermal characteristics of the fixture in which it has been installed.

*Lamp dimming profiles subject to ballast type and environmental condition. Contact Lunera for more detailed information.


Photometry

Optical data is based on performance of bare lamps.

Polar Candela Distribution [20,000lm / 15,000lm]



Polar Candela Distribution [9,000lm / 4,500lm]



Intended Applications

The Lunera HID LED lamp is designed to replace Metal Halide (MH) and High Pressure Sodium (HPS) lamps in the following compatible applications:

Wattage Compatibilities	Sockets	Power Source	Mount
Lunera HID LED Mogul (E39) Base  400W - 70W MH or HPS	E39 / EX39 Mogul 	Magnetic HID Ballast 	Vertical Mount High Bay / Low Bay Fixture Type   High Bay Low Bay

Application Notes

The Lunera HID LED lamp can be used in open and fully enclosed fixtures.

This device is NOT rated for use with dimmers.

Lunera HID LED Lamps supports operation with following ballasts:

Ballast Type	Ballast Input Voltage	Ballast Wattage
Constant Wattage Autotransformer (CWA)	480V ~ 120V	400W ~ 70W
High Reactance (HX)	277V ~ 120V	400W ~ 70W

Contact Lunera for luminaire level IES files with high bay. and low bay DLC referenced fixtures.

Lunera HID LED lamp does NOT support operations with electronic HID ballasts.

This product is NOT intended for use with emergency lighting or for emergency lighting.


Caution

Turn power off when installing this lamp.

Product Dimensions

Measurements are exact. Dimensions are shown in millimeters and inches. Please contact your Lunera representative for other product dimensions.

Vertical E39 Lamp Standard Body/Heatsink 20,000lm / 15,000lm



Sample Part Numbers:

SN-V-E39-B-20KLM-8XX-G3
SN-V-E39-B-15KLM-8XX-G3

'XX' : may be 35 (3500K), 40 (4000K), or 50 (5000K)

CAUTION

Turn off power when installing the lamp.

For FAQ and Technical Support, please visit:
<https://lunera.freshdesk.com/support/home>

© 2016 Lunera Lighting, Inc. All Rights Reserved. Lunera and the Lunera logo are registered trademarks; Lunera TruColor and Thermal IQ, are trademarks of Lunera Lighting, Inc. All other trademarks are the property of their respective owners.

Specifications are subject to change without notice. This document is for informational purposes only.

For Technical Support:


<https://lunera.com/freshdesk.com/support/home>

R091116 © 2016 Lunera® Lighting

www.lunera.com

T (650) 241-3874

Vertical E39 Lamp Short Body/Heatsink 9,000lm / 4,500lm



Sample Part Numbers:

SN-VS-E39-B-9KLM-8XX-G3
SN-VS-E39-B-4.5KLM-8XX-G3

'XX' : may be 35 (3500K), 40 (4000K), or 50 (5000K)

