

Presented By: Candela Corporation
Contact Phone: 800-922-9226
Contact E-mail: sales@candelacorp.com


Customer Name:
Project Name:
Fixture Type:



GE
Lighting

16920 - SPL1500/H/652

GE Quartz Metal Halide T7 - Sports Lighting



CAUTIONS & WARNINGS

Caution

- Risk of Burn
 - Allow lamp to cool before handling.
 - Do not turn on lamp until fully installed.
- Lamp may shatter and cause injury if broken
 - Do not use lamp if outer glass is scratched or broken.
 - Do not use excessive force when installing lamp.

Warning

- Unexpected lamp rupture may cause injury, fire, or property damage
 - Do not exceed rated voltage.
 - Do not touch glass with bare hands.
 - Do not use where directly exposed to water or outdoors without an enclosed fixture.
 - Use in enclosed fixture rated for this product.
 - Do not use lamp if outer glass is scratched or broken.
 - Use only properly rated ballast.
 - Operate lamp only in specified position.
 - Turn lamp off at least once for 15 minutes per week.
 - Do not turn on lamp until fully installed.
- Lamp emits UV radiation which may cause eye/skin injury. RG-3
 - Avoid exposure of eyes and skin to unshielded lamp.
- Risk of Fire
 - Keep combustible materials away from lamp.
 - Use in fixture rated for this product.
- Risk of Electric Shock
 - Turn power off before inspection, installation or removal.
 - Do not use where directly exposed to water or outdoors without an enclosed fixture.

NOTES

- Requires a non-ANSI designated ballast with a special, add-on metal halide ignitor. Contact your local GE Representative for a list of approved ballasts and ignitors.

GENERAL CHARACTERISTICS

Lamp Type	High Intensity Discharge - Quartz Metal Halide
Bulb	T7
Base	Rx7s
Bulb Finish	Inside frost
Rated Life (MIN)	6000.0 h
Rated Life (Vert)	6000.0 h
Rated Life (NOM)	6000.0 h
Rated Life (Hor)	6000.0 h
Lamp Enclosure Type (LET)	Enclosed fixtures only
Mercury Content (NOM)	47.5 mg
Picograms of Mercury (NOM)	88.0 pg
Primary Application	Sports Lighting

PHOTOMETRIC CHARACTERISTICS

Initial Lumens (Vert)	120000.0
Initial Lumens (NOM)	120000.0
Initial Lumens (Hor)	80.0
Mean Lumens (NOM)	90000.0
Nominal Initial Lumens per Watt (NOM)	80.0
Color Temperature (NOM)	5200.0 K
Color Rendering Index (CRI) (NOM)	65.0

ELECTRICAL CHARACTERISTICS

Wattage (NOM)	1500.0
Burn Position	Horizontal
Warm Up Time to 90% (NOM)	2.0 min

DIMENSIONS

Maximum Overall Length (MOL) (NOM)	10.120 in(257.0 mm)
Bulb Diameter (DIA) (MAX)	0.875 in(22.2 mm)
Light Center Length (LCL) (NOM)	5.000 in(127.0 mm)

PRODUCT INFORMATION

Product Code	16920
Description	SPL1500/H/652
ANSI Code	HID
Standard Package	Case
Standard Package GTIN	10043168169209
Standard Package Quantity	1
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard	1
Package	
UPC	043168169202