



Energy-Efficient Direct Incandescent Replacement StackLED® LED Lamps

U.S. Patent No. 5,577,832; Des. 404,506

Series STL602 (15mm DC Bayonet Base)	BA15D	Part Number	LED Color Code*	Volts**	Current (mA)	Total mcd	Use on†	
		STL602-01-01	RED ●	24V BP	60	1475	Siemens	
		STL602-02-01	AMBER ●	24V BP	60	850		Square D Company/ Telemecanique Inc. (XVAL series)
		STL602-03-01	GREEN ●	24V BP	45	4800		
		STL602-04-01	YELLOW ●	24V BP	60	1400		
		STL602-05-01	BLUE ●	24V BP	45	1525		
		STL602-06-01	WHITE ○	24V BP	45	1920		
		STL602-01-02	RED ●	120VAC	20	1475	PATLITE/Sasaki Electric (LH & WM series)	
		STL602-02-02	AMBER ●	120VAC	20	850		
		STL602-03-02	GREEN ●	120VAC	15	4800		
		STL602-04-02	YELLOW ●	120VAC	20	1400	Joslyn Clark (SL System)	
		STL602-05-02	BLUE ●	120VAC	15	1525		
		STL602-06-02	WHITE ○	120VAC	15	1920	Tork	
		STL602-01-03	RED ●	12V BP	60	1475		
		STL602-02-03	AMBER ●	12V BP	60	850		
		STL602-03-03	GREEN ●	12V BP	90	4800	Klockner Moeller	
		STL602-04-03	YELLOW ●	12V BP	60	1400		
		STL602-05-03	BLUE ●	12V BP	90	1525		
		STL602-06-03	WHITE ○	12V BP	90	1920		
		STL603-01-01	RED ●	24V BP	60	1475	PATLITE/Sasaki Electric (ST series)	
		STL603-02-01	AMBER ●	24V BP	60	850		
		STL603-03-01	GREEN ●	24V BP	45	4800		
		STL603-04-01	YELLOW ●	24V BP	60	1400		
		STL603-05-01	BLUE ●	24V BP	45	1525		
		STL603-06-01	WHITE ○	24V BP	45	1920		
		STL603-01-02	RED ●	120VAC	20	1475	PATLITE/Sasaki Electric (ST series)	
		STL603-02-02	AMBER ●	120VAC	20	850		
		STL603-03-02	GREEN ●	120VAC	15	4800		
		STL603-04-02	YELLOW ●	120VAC	20	1400	Joslyn Clark (SL System)	
		STL603-05-02	BLUE ●	120VAC	15	1525		
		STL603-06-02	WHITE ○	120VAC	15	1920	Tork	
		STL603-01-03	RED ●	12V BP	60	1475		
		STL603-02-03	AMBER ●	12V BP	60	850		
		STL603-03-03	GREEN ●	12V BP	90	4800	Klockner Moeller	
		STL603-04-03	YELLOW ●	12V BP	60	1400		
		STL603-05-03	BLUE ●	12V BP	90	1525		
		STL603-06-03	WHITE ○	12V BP	90	1920		
		STL609-01-01	RED ●	24V BP	60	1475	PATLITE/Sasaki Electric (ST series)	
		STL609-02-01	AMBER ●	24V BP	60	850		
		STL609-03-01	GREEN ●	24V BP	45	4800		
		STL609-04-01	YELLOW ●	24V BP	60	1400		
		STL609-05-01	BLUE ●	24V BP	45	1525		
		STL609-06-01	WHITE ○	24V BP	45	1920		
		STL609-01-02	RED ●	120VAC	20	1475	PATLITE/Sasaki Electric (ST series)	
		STL609-02-02	AMBER ●	120VAC	20	850		
		STL609-03-02	GREEN ●	120VAC	15	4800		
		STL609-04-02	YELLOW ●	120VAC	20	1400	Joslyn Clark (SL System)	
		STL609-05-02	BLUE ●	120VAC	15	1525		
		STL609-06-02	WHITE ○	120VAC	15	1920	Tork	
		STL609-01-03	RED ●	12V BP	60	1475		
		STL609-02-03	AMBER ●	12V BP	60	850		
		STL609-03-03	GREEN ●	12V BP	90	4800	Klockner Moeller	
		STL609-04-03	YELLOW ●	12V BP	60	1400		
		STL609-05-03	BLUE ●	12V BP	90	1525		
		STL609-06-03	WHITE ○	12V BP	90	1920		

* Color codes listed reflect the status indicator lens colors.

** BP (Bipolar) can be used with AC or DC power

† Part numbers listed are recommended retrofits to a specific manufacturer's stack holder model and are designed specifically to operate in those models

Log # 015B Rev 09-2000

