

Electronic Ballast for T5 HO Lamps

- UL, cUL Listed
- Sound Rated A
- Lamp Current Crest Factor < 1.70
- End of Lamp Life Protection
- Ballast Factor > 1.0
- Class P
- Outdoor Type 1



- EMI: Meet FCC Title 47, Part 18
- Can Size # 1: 9.50" L x 1.30" W x 1.00" H Mounting Center: 8.91"

T5 HO		120V ~ 277V		Programmable Start				
Model # Order Code	Input Voltage	Lamp Qty	Lamp Type	Input Watts	Line Amps max	Power Factor	THD %	Can Size
U-2/24T5HO	120 ~ 277	2	24W T5HO, 1xTT36W	51	0.43			
U-2/39T5HO	120 ~ 277	2	39W T5HO, 24W T5HO, 1xTT36W	81	0.69	> 1.0	< 10	#1
U-2/54T5HO	120 ~ 277	2	54W T5HO	110	0.93			
U-3/54T5HO	120 ~ 277	3	54W T5HO					

Electronic Ballast for T5 HE Lamps

- UL, cUL Listed
- Sound Rated A
- Lamp Current Crest Factor < 1.70
- Ballast Factor > 0.88
- End of Lamp Life Protection
- Outdoor Type 1
- FCC Class B
- Can Size #6 - 10.35" L x 1.24"W x 1.00"H Mounting Center - 10.00"
- Can Size #10 - 8.30" L x 0.95"W x 0.90"H Mounting Center - 7.95"



T5 HE		120V		Preheat Start				
Model # Order Code	Input Voltage	Lamp Qty	Lamp Type / Wattage	Input Wattage	Line Amps	Power Factor	THD %	Can Size
T5120-228	120V	1 or 2	F28/T5, 28W	54	0.90			
			F21/T5, 21W	40	0.67	> 0.50	140	#6
T5120-214	120V	1 or 2	F14/T5, 14W	26	0.43			
120-814	120V	1	F8T5	8	0.13			
			F13T5 or F14T5	14	0.23			
120-2128	120V	1	F21T5, 21W	21	0.35	> 0.50	140	#10
			F28T5, 28W	28	0.47			
120-1626	120V	2	F8T5, 8W or F13T5 13W	16	0.27			
		2	F8T5, 8W + F13T5 13W	26	0.43			