PHENOLIC INCANDESCENT SOCKETS

Pull Chain with Outlets

A. L1406B - Black **B. L1406-**Ivory
250W 125V

- **A. (T1) Keyless** 660W-250V
- **B. (T2) Pull Chain** 250W-250V
- **C. (T3) 3-Way** 250W-250V
- **D. (T4) Single Circuit** 250W-250V

Ring 2-1/8" O.D. included, socket height 2-5/8", socket thread slips 1-3/8" minimum, 1/8" IP

CANDELABRA SOCKETS

Twin Cluster
LD1019
3-1/4" end to end 1/8 IPS tapped bracket 75W-125V

Hickey Sockets
75W-125V leads-18ga.

L150-2
1-3/4" High 24" Leads, 150 C°

L10017-62F
1-3/4" High Leads 24", 105 C°

L10017-241F
3" High Leads 24", 105 C°

L10017-204F
4" High Leads 24", 105 C°

Candelabra Phenolic Socket
Sockets have Screw Terminals Insulators included 75W 125V

- **A. L10027** -1-3/4" High domestic
- **B. L10025** -Height 2" domestic
- **B1. L10025-2** - Height 2" import
- **C. L10026** -domestic
- **C1. L10026-2** - import

Adjustable 3-1/2" to 4-5/8"

Porcelain with Screw Terminals
approved for 170 C°. applications 75W-125V

L20025 -height 2-3/32"
Adjustables
A. L20026 -3-1/2"- 4-5/8"
B. L20026-2 -4-1/2"-5-1/2"

Harness Set
L10032-500
75W-250V
1 to 500 cut to order 13" center to center

Threaded Body Sockets Candelabra
L10032F
Plastic Nut Included

Molded Plastic Nut
BA23569