

T Series

Sunlite 80617 LED Filament T10 Tubular Light Bulb, 6 Watts (60W Equivalent), 570 Lumens, Medium E26 Base, 120 Volts, Dimmable, 90 CRI, UL Listed, 2200K Amber White, 1 Pack

Filament

DESCRIPTION:

Save on energy costs for your house, business, restaurant, hotel and more, with Sunlite's energy efficient antique style tubular LED light bulbs. By changing your incandescent or fluorescent tube lights for Sunlite's LED filament lamps, not only will you save on energy costs, but you will also reduce the effects of aging and eliminate the chances of mercury exposure. These Edison bulbs operate at a modest 6 watts and produce a 2200K amber light while outputting a nice 570 lumen brightness. Dimensions 8.74" Height x 1.18" Diameter.

FEATURES:

- **UPGRADE TO LED** – These dimmable, Edison style, antique, 6 watts T10 tubular LED bulbs are an energy efficient replacement for 60-watt incandescent bulbs. They have a medium (E26) base and remain cool to the touch even when lit. They are instant-on at full 570 lumen brightness.
- **SAVE ENERGY** – The antique style tubular LED light bulbs have the same light output of a 60-watt incandescent bulb while saving 87% on electricity. The annual energy cost is a low 72 cents per year (Based on 3 hours/day at \$.11 per/kWh).
- **LONG LIFE SPAN** – With an average life span of 15,000 hours you'll need to replace hard to reach bulbs less often. Perfect for showcase lighting, bar and restaurant lighting, and other indoor lighting fixtures.
- **AMBER LIGHT** – At 2200K the lighting temperature of these amber LED filament bulbs provide a comforting glow in bedrooms, living rooms, or anywhere you want to set relaxed mood. 90 CRI.
- **THE SAFER CHOICE** – These indoor, vintage looking, bulbs are UL Listed for dry location installation. Ideal for both residential and commercial use. Dimensions 8.74" Height x 1.18" Diameter.



SPECIFICATIONS:

General Characteristics

Bulb Shape	T10
Average Rated Hours	15000
Finish	Clear
Base	Medium Screw (E26)
Average Life Span Years	14
Ingress Protection	IP20 (12.5 mm solids, Not protected from liquids)
Dimmable	Yes
Dimming Type	Forward Phase (Triac or Incandescent)
Material	Glass

Product Dimensions

MOL (in)	8.74
Diameter (in)	1.18
Item Dimension (in)	(W) 1.18 (H) 8.74 (D) 1.18
Package Dimension (in)	(W) 7.7 (H) 10.4 (D) 3.3
Package Weight (lb)	2

Product Data

Case Unit Rate	10
Pack Size	1
Item UPC	653703806174

Electrical Characteristics

Amps	0.062
Watts	6
Volts	120
Equivalent Wattage	60
Power Factor	0.7
Temperature	-4°F - 104°F

Light Characteristics

Lumens Brightness	570
Color Rendering Index CRI	90
Emitted Color	Amber Light
Color Temperature Kelvin	2200
Beam Angle	360
Beam Angle Description	Omni-Directional

Additional Features

Safety Rating Mark	UL Listed - Wet Location
UL Rated Enclosed Fixtures	Yes
Safety Rated For USA	Yes
Title 20	Lawful for sale in California
Rohs Compliant	Yes
Mercury Free	Yes

