

LED Lamps

ProLED® T8 Linear Type-A

- 2', 3', 4' Options
- No Re-Wiring Necessary
- Instant On - No Flicker
- 5-Year Warranty

Specifications

Product Description

The QuickConnect Type A lamp operates on most instant start and electronic ballasts, making LED lighting retrofit easier than ever.

Construction:

- Glass Lens
- 2', 3' and 4' Metal End Caps

Installation:

- Quick Plug&Play Installation
- Refer to ballast Compatibility Chart for Compatible Ballasts
- Suitable for use in Totally Enclosed Luminaires

Quick
CONNECT
Type A



Easy To Install



Food Equipment
Certification



50,000 Hours



Direct Ballast
Compatible



RECOGNIZED
COMPONENT
Intertek
4005203
conforms to IEC 60528
Made in China



DLC Qualified

Performance

- Operates on Compatible T8 Instant Start, Programmed Start and Emergency Ballasts
- 120-277V
- 8W, 11W, 12W Option (2', 3', 4')
- 1325 - 2000 Lumens
- L70>50,000
- 82 CRI
- Dimmable (4' only)

Certifications:

- cUL Approved for Damp Locations
- Conforms to Requirements of NSF/ANSI Standard 2 Food Equipment
- DLC Qualified. Refer to designlights.org for Full List of Qualified Products.
- 5 Year Warranty

LED Lamps



ProLED T8 Linear Type-A

Ordering Logic

Product Description

Lamp Size and Wattage	-	CCT	-	Lamp Type	-	Source
T824FR8 = 2' 8W T836FR10 = 3' 11W T824FR13 = 4' 12W	-	835 = 82 CRI, 3500K 840 = 82 CRI, 4000K 850 = 82 CRI, 5000K	-	DIR = Direct Replacement	-	LED = LED Source

Stock Guide

Watt	System Watt	Base	Product #	Product Code	Description	Voltage	CCT	CRI	Lumens	Useful Life	Pkg. Qty.	MOL	Equivalent Wattage	End Cap
8	11	G13	82355	T824FR8/835/DIR3/LED	T8 Linear QuickConnect 3500K	120-277V	3500K	82	1325	50,000	1/25	24"	17	Metal
8	11	G13	82356	T824FR8/840/DIR3/LED	T8 Linear QuickConnect 4000K	120-277V	4000K	82	1350	50,000	1/25	24"	17	Metal
8	11	G13	82357	T824FR8/850/DIR3/LED	T8 Linear QuickConnect 5000K	120-277V	5000K	82	1350	50,000	1/25	24"	17	Metal
11	14	G13	82358	T836FR11/835/DIR3/LED	T8 Linear QuickConnect 3500K	120-277V	3500K	82	1675	50,000	1/25	36"	25	Metal
11	14	G13	82359	T836FR11/840/DIR3/LED	T8 Linear QuickConnect 4000K	120-277V	4000K	82	1700	50,000	1/25	36"	25	Metal
11	14	G13	82360	T836FR11/850/DIR3/LED	T8 Linear QuickConnect 5000K	120-277V	5000K	82	1700	50,000	1/25	36"	25	Metal
12	14	G13	83880	T8FR12/835/DIR4/LED	T8 Linear QuickConnect 3500K	120-277V	3500K	82	1800	50,000	1/25	48"	32	Metal
12	14	G13	83881	T8FR12/840/DIR4/LED	T8 Linear QuickConnect 4000K	120-277V	4000K	82	1900	50,000	1/25	48"	32	Metal
12	14	G13	83882	T8FR12/850/DIR4/LED	T8 Linear QuickConnect 5000K	120-277V	5000K	82	2000	50,000	1/25	48"	32	Metal

Dimensions

* For more detail visit
 installation instructions

