



fulham® THORLED™

LED DRIVERS

Applications

- Signage/Channel Letters
- Undercabinet
- Sconce
- Refrigerated Cases
- Recessed Ceiling Fixtures
- Pathway

Constant Voltage Drivers

- High Efficiency
- 50,000 Hour Service Life
- Reliability & Flexibility
- 12V, 24V & 48V
- 5 Year Warranty



Constant Current Drivers

- Triac and 0-10V Dimming (select models)
- Optimized System Efficiency
- Single or Multiple Outputs for Greater Flexibility
- High Efficiency
- Low Temperature Performance (select models)
- UL Class 2
- Compact Size
- 50,000 Hour Service Life



Constant Current Single and Multiple Outputs

	TC1120 0350 6 C	TC1120 0350 15 C	TC1120 0700 18 C	TC3120 0500 75 LA
cURus	✓		✓	
Input Voltage	120V	120V	120V	120V
Frequency	50/60Hz	50/60Hz	50/60Hz	50/60Hz
Number of Channels	1	1	1	3
Output Wattage	6	15	18	75
Output Volts	6~20VDC	24~50VDC	11~30VDC	20~50VDC
Output Current (mA)	350	350	700	500
Driver Size	L 1.8", W 1.8", H 1" L 46mm, W 46mm, H 25mm	L 2.6", W 1.8", H 1" L 66mm, W 46mm, H 25mm	L 3.2", W 2.4", H 1" L 81mm, W 61mm, H 25mm	L 12", W 1.7", H 1" L 305mm, W 43mm, H 25mm
Case Material	Metal	Metal	Metal	Metal
Min. Operating Temp	-20°C	-20°C	-20°C	-30°C
Max. Case Temp	70°C	70°C	75°C	75°C