



116, 117, 118, 119 Series Ceiling Fixture Specifications

T6 and T9 Circline Lamps

- 10,000 hours lamp life, 50,000 hours ballast life

Item #	Description	Ballast Wattage	Lamp Wattage	Incandescent Wattage Comparison	Initial Lumens	Input Line Current	Replacement Lamp	Replacement Ballast
11622WH	★ 10" White Plate w/ Plastic Dome Cover	22	22	75	1400	.30A	32022	17022Q
1163032WH	10" White Plate w/ Plastic Dome Cover	30	32	130	2200	.49A	32032	17030Q
11630WH	★ 10" White Plate w/ Plastic Dome Cover	30	30	120	2000	.44A	32030	17030Q
11640WH	★ 10" White Plate w/ Plastic Dome Cover	40	40	150	2800	.66A	32040	17040Q
11722WH	★ 14" White Ring Base w/ Plastic Dome Cover	22	22	75	1400	.30A	32022	17022Q
1173032WH	14" White Ring Base w/ Plastic Dome Cover	30	32	130	2200	.49A	32032	17030Q
1173032WHHP	14" White Ring Base w/ Plastic Dome Cover	30	32	130	2200	.49A	32032	12530Q
11730WH	★ 14" White Ring Base w/ Plastic Dome Cover	30	30	120	2000	.44A	32030T6	17030Q
11730WHHP	14" White Ring Base w/ Plastic Dome Cover	30	30	120	2000	.25A	32030T6	12530Q
11732WH	★ 14" White Ring Base w/ Plastic Dome Cover	32	32	130	2200	.49A	32032	17030Q
11740WH	★ 14" White Ring Base w/ Plastic Dome Cover	40	40	150	2800	.66A	32040	17040Q
11822PB	★ 14" Polished Brass Step Base w/ Plastic Dome Cover	22	22	75	1400	.30A	32022	17022Q
11830PB	★ 14" Polished Brass Step Base w/ Plastic Dome Cover	30	30	120	2000	.44A	32030	17030Q
11830WH	★ 14" White Step Base w/ Plastic Dome Cover	30	30	120	2000	.44A	32030	17030Q
11830BS	★ 14" Brushed Steel Step Base w/ Plastic Dome Cover	30	30	120	2000	.44A	32030	17030Q
1193032ABHP	14" Antique Brass Step Base w/ Plastic Swirl Cover	30	32	130	2200	.33A	32032	12530Q
1193032PB	14" Polished Brass Step Base w/ Plastic Swirl Cover	30	32	130	2200	.49A	32032	17030Q
1193032WHHP	14" White Step Base w/ Plastic Swirl Cover	30	32	130	2200	.33A	32032	12530Q
11930ABHP	14" Antique Brass Step Base w/ Plastic Swirl Cover	30	30	120	2000	.25A	32030	12530Q
11930PB	★ 14" Polished Brass Step Base w/ Plastic Swirl Cover	30	30	120	2000	.44A	32030	17030Q
11930WHHP	14" White Step Base w/ Plastic Swirl Cover	30	30	120	2000	.25A	32030	12530Q
11940PB	★ 14" Polished Brass Step Base w/ Plastic Swirl Cover	40	40	150	2800	.66A	32040	17040Q



Specifications (at full brightness)

End of Life Protection	Yes
Ballast Type	Electronic
Starting Method	Modified Rapid Start
Input Line Voltage	120VAC
Input Line Frequency	50/60HZ
Lamp Life (rated)	10,000 Hours
Ballast Life (rated)	50,000 Hours
Color Temperature	2850°K
Color Rendering Index	84
Minimum Starting Temperature	-20 ° F
Maximum Operating Temperature	160 ° F
U.L. / C.U.L. Listed	Yes
FCC Compliance	Part 18, Subpart C
Lamp Operating Frequency	45 KHZ
Lamp Current Crest Factor	< 1.60
Maximum Open Circuit Voltage	600V
Power Factor	>.50
Total Harmonic Distortion	< 150%

Applications:

- Use anywhere a standard incandescent ceiling fixture is used.
- Bedrooms, Hallways, Kitchens Living Rooms, Recreation Rooms

Features and Benefits:

- Long life, 10,000 hour average rated bulb life
50,000 hour average rated ballast life
- Bulb lasts 7 years, based on 4 hours use per day
- Bulb lasts 10 times longer than similar incandescent bulbs
- 2850°K color temperature closest to incandescent light
- Quick run-up time
- Instant start, flicker free
- Replaceable Ballast, Snap-in / No wiring
- World class phosphor insures high lumen output and excellent lumen maintenance
- UL Damp Location Rated



ISO 9002
CERTIFIED

2 YEAR
WARRANTY

TCP, Inc.

325 Campus Dr. | Aurora, Ohio 44202 | www.tcp.com | Customer Service: 800.771.9335

©TCP, Inc. 2008/02693