

Dimmable
TCP PRO SERIES DIMMABLE FULL SPRING LAMPS, HPF, 10,000 HOUR


Item Number	ENERGY STAR® Item Description	Unit/Ballast Watts	Incandescent Comparison (Watts)	Initial Lumens	CCT (Kelvin)	CRI	MOL/Height (Inches)	Diameter/Width (Inches)	Base Type	Case Quantity
40114	14 Watt Dimmable Full Spring	14	60	850	2700	82	4.4	2.0	E26	12
40123	23 Watt Dimmable Full Spring	23	100	1500	2700	82	4.9	2.4	E26	12

TCP PRO SERIES DIMMABLE COVERED LAMPS, HPF, 8,000 HOUR


Item Number	ENERGY STAR® Item Description	Unit/Ballast Watts	Incandescent Comparison (Watts)	Initial Lumens	CCT (Kelvin)	CRI	MOL/Height (Inches)	Diameter/Width (Inches)	Base Type	Case Quantity
2R2014DIM	14 Watt R20 Dimmable	14	50	410	2700	82	5.1	2.5	E26	12
2R3016DIM	16 Watt R30 Dimmable	16	65	650	2700	82	5.4	3.7	E26	12
2R4019DIM	19 Watt R40 Dimmable	19	85	900	2700	82	6.1	4.8	E26	12
2G2514DIM	14 Watt G25 Dimmable	14	60	750	2700	82	5.2	3.1	E26	6

NEW Pro Series Dimmable

These CFLs combine powerful performance with intelligent design. We created these new dimmable CFLs to meet the most demanding applications. **Full dimming performance** all the way down to 20% with no annoying flicker – that's best in class performance!

Features & Benefits

- Uniform, smooth dimming performance from 100% to 20%.
- Optimized electronics maximizes lamp life and increases lumen output.

TCP Pro Dimmable Series is available in the following color temperatures:

- 2700°K
- 3000°K
- 3500°K
- 4100°K
- 5000°K
- 6500°K