

## Compact Fluorescent PL Lamp

- 10,000 Hours average rated life

| Item #     | Wattage | Description                      | Base Type | Initial Lumens | M.O.L. (inches) | Diameter (inches) |
|------------|---------|----------------------------------|-----------|----------------|-----------------|-------------------|
| 32005      | 5       | Twin Tube, 2-pin                 | G23       | 250            | 4.10            | 1.05              |
| 32007†     | 7       | Twin Tube, 2-pin                 | G23       | 400            | 5.25            | 1.25              |
| 32009†     | 9       | Twin Tube, 2-pin                 | G23       | 570            | 6.44            | 1.25              |
| 32013†     | 13      | Twin Tube, 2-pin                 | GX23      | 825            | 6.88            | 1.25              |
| 32013IST†  | 13      | Twin Tube, 2-pin, Instant start* | GX23      | 825            | 6.88            | 1.25              |
| 32413/2Gx7 | 13      | Twin Tube, 4-pin                 | 2Gx7      | 800            | 7.13            | 1.25              |
| 32009Q     | 9       | Quad Tube, 2-pin                 | G23-2     | 600            | 4.27            | 1.05              |
| 32013Q†    | 13      | Quad Tube, 2-pin                 | GX23-2    | 825            | 5.15            | 1.35              |
| 32013ISQ†  | 13      | Quad Tube, 2-pin, Instant start* | GX23-2    | 825            | 4.62            | 1.35              |
| 32018Q     | 18      | Quad Tube, 2-pin                 | G24d-2    | 1100           | 6.00            | 1.05              |
| 32022Q     | 22      | Quad Tube, 2-pin                 | GX32d-2   | 1000           | 5.80            | 1.73              |
| 32026Q†    | 26      | Quad Tube, 2-pin                 | G24d-3    | 1800           | 6.63            | 1.35              |
| 32028Q     | 28      | Quad Tube, 2-pin                 | GX32d-3   | 1400           | 6.46            | 1.73              |
| 32413Q†    | 13      | Quad Tube, 4-pin                 | G24q-1    | 860            | 5.15            | 1.35              |
| 32418Q†    | 18      | Quad Tube, 4-pin                 | G24q-2    | 1200           | 6.63            | 1.35              |
| 32426Q     | 26      | Quad Tube, 4-pin                 | G24q-3    | 1600           | 6.31            | 1.05              |
| 32418T     | 18      | Triple Tube, 4-pin               | GX24q-2   | 1150           | 4.25            | 1.40              |
| 32426T     | 26      | Triple Tube, 4-pin               | GX24q-3   | 1650           | 4.78            | 1.55              |
| 32432T     | 32      | Triple Tube, 4-pin               | GX24q-3   | 2000           | 5.50            | 1.60              |
| 32442T     | 42      | Triple Tube, 4-pin               | GX24q-4   | 2400           | 6.00            | 1.60              |

\* TCP's instant start PL lamp has an electronic instant starter for instant-on when used with a magnetic ballast.

Use Color temperature suffix with part # to specify color temperature when ordering.

( 27K= 2700°K, 30K = 3000°K, 35K = 3500°K, 41K = 4100°K, 50K = 5000°K, 65K =6500°K )

### Features and Benefits

- Long life, 10,000 hour average rated life
- Lasts 7 years, based on 3 hours use a day
- Bulb lasts 10-13 times longer than similar incandescent bulbs
- 2700°K color temperature closest to incandescent light
- Also available in 2700°K, 3000°K, 3500°K, 4100°K, 5000°K and 6500°K (To order use item # with suffix 27K, 30K, 35K, 41K, 50K or 65K)

† Meets ANSI-IEC CT8.901

### Specifications ( at full brightness )

Lamp Life (rated) ----- 10,000 Hours  
 Color Temperature ----- 2700 K\*\*  
 Color Rendering Index ----- 82  
 \*\* Other color temperatures available

**12** MONTH  
WARRANTY

