



Torchiere Specifications

65 Watt Torchiere with advanced T6 Circline Lamps


• 10,000 Hours lamp life, 50,000 Hrs. ballast life

3 way light levels (30 / 36 / 65 Watts)
(1800 / 2200 / 4000 Lumens)

Incandescent comparison
(100 / 130 / 200 Watts)

Item #	Finish	Ballast Wattage*	Lamp Lumens*	Input Line Current	Replacement Lamps	Replacement Ballast
53065WH ★	White	65	4000	.92A	32032/32027	16565Q
53065BK ★	Black	65	4000	.92A	32032/32027	16565Q
53065BS ★	Steel	65	4000	.92A	32032/32027	16565Q

* With switch set to highest setting



Features and Benefits:


- New 65 watt compact fluorescent ballast and lamps offer the brightest Torchiere ever.
- TCP ballasts low operating temperature ensure long ballast life.
- Advanced T6 lamps with world class phosphor guarantees a brilliant color and brightness.
- Excellent replacement for quartz halogen Torchieres. Low operating temperature makes this Torchiere ideal for children's areas.

Special Application Options:

- Use anywhere as a floor lamp. Provides indirect light.
- Perfect for living rooms, dining rooms, dorms and children's areas.

Specifications (at full brightness)

Ballast Type -----	Electronic
Starting Method -----	Modified Rapid Start
Input Line Voltage -----	120VAC
Input Line Frequency -----	60HZ
Lamp Life (rated) -----	10,000 Hours
Ballast Life (rated) -----	50,000 Hours
Color Temperature -----	2850°K
Color Rendering Index -----	83
Minimum Starting Temperature -----	-20 ° F
Maximum Operating Temperature -----	160 ° F
U.L. / C.U.L. Listed -----	Yes
FCC Compliance -----	Part 18, Subpart C
Lamp Operating Frequency -----	45 KHZ
Lamp Current Crest Factor -----	< 1.60
Maximum Open Circuit Voltage -----	600V
Power Factor -----	> .50
End of Life Protection -----	Yes
Total Harmonic Distortion -----	< 150%



13"

13" diameter reflector spreads a wide, bright indirect light

3 way switch

72"

Screw-in pole sections make it easy to assemble or disassemble for moving

3 popular finishes - White, Black and Brushed Steel

Standard 120 volt input line voltage

Stable, weighted base

11"



ISO 9002
CERTIFIED

2 YEAR
WARRANTY

TCP, Inc.

325 Campus Dr. | Aurora, Ohio 44202 | P: 800-324-1496 | F: 330-995-6188 | www.tcpinc.com

©TCP, Inc. 2008/02615