




NPF Track Light Fixture Heads Specifications


2-Piece SpringLamp® – 4 pin, NPF Compact Fluorescent, 10,000 hours lamp life

- Use anywhere for adjustable, directional lighting.
Perfect for: Kitchens, Bathrooms, Living Rooms & Recreation Rooms


Item #	Watts	Incandescent Wattage Comparison	Description	Initial Lumens	Input Line Current	Power Factor	Dimming	Replacement Lamps
59211WH	11	52	R20 White Juno head	400	.16A	> .50	No	35011
59211BK	11	52	R20 Black Juno head	400	.16A	> .50	No	35011
59311WH	11	52	R20 White Halo head	400	.16A	> .50	No	35011
59311BK	11	52	R20 Black Halo head	400	.16A	> .50	No	35011
59411WH	11	52	R20 White Lightolier head	400	.16A	> .50	No	35011
59411BK	11	52	R20 Black Lightolier head	400	.16A	> .50	No	35011
59214WH	14	60	R30 White Juno head	600	.20A	> .50	No	35014
59214BK	14	60	R30 Black Juno head	600	.20A	> .50	No	35014
59314WH	14	60	R30 White Halo head	600	.20A	> .50	No	35014
59314BK	14	60	R30 Black Halo head	600	.20A	> .50	No	35014
59414WH	14	60	R30 White Lightolier head	600	.20A	> .50	No	35014
59414BK	14	60	R30 Black Lightolier head	600	.20A	> .50	No	35014
59218WH	18	75	R40 White Juno head	860	.29A	> .50	No	35018
59218BK	18	75	R40 Black Juno head	860	.29A	> .50	No	35018
59318WH	18	75	R40 White Halo head	860	.29A	> .50	No	35018
59318BK	18	75	R40 Black Halo head	860	.29A	> .50	No	35018
59418WH	18	75	R40 White Lightolier head	860	.29A	> .50	No	35018
59418BK	18	75	R40 Black Lightolier head	860	.29A	> .50	No	35018
59223WH	23	90	R40 White Juno head	1050	.35A	> .50	No	35023
59223BK	23	90	R40 Black Juno head	1050	.35A	> .50	No	35023
59323WH	23	90	R40 White Halo head	1050	.35A	> .50	No	35023
59323BK	23	90	R40 Black Halo head	1050	.35A	> .50	No	35023
59423WH	23	90	R40 White Lightolier head	1050	.35A	> .50	No	35023
59423BK	23	90	R40 Black Lightolier head	1050	.35A	> .50	No	35023
59226WH	26	100	R50 White Juno head	1310	.45A	> .50	No	35026
59226BK	26	100	R50 Black Juno head	1310	.45A	> .50	No	35026
59326WH	26	100	R50 White Halo head	1310	.45A	> .50	No	35026
59326BK	26	100	R50 Black Halo head	1310	.45A	> .50	No	35026
59426WH	26	100	R50 White Lightolier head	1310	.45A	> .50	No	35026
59426BK	26	100	R50 Black Lightolier head	1310	.45A	> .50	No	35026
59232WH	32	130	R50 White Juno head	1575	.49A	> .50	No	35032
59232BK	32	130	R50 Black Juno head	1575	.49A	> .50	No	35032
59332WH	32	130	R50 White Halo head	1575	.49A	> .50	No	35032
59332BK	32	130	R50 Black Halo head	1575	.49A	> .50	No	35032
59432WH	32	130	R50 White Lightolier head	1575	.49A	> .50	No	35032
59432BK	32	130	R50 Black Lightolier head	1575	.49A	> .50	No	35032



Track Light Fixture Head
includes track connector
reflector, SpringLamp®
and diffuser




Reflector




2 Piece
SpringLamp


Diffuser
Lens



Juno Connector



Halo Connector



Lightolier Connector

Features and Benefits

- Long life, 10,000 hour average rated lamp life
50,000 hour average rated ballast life
- Lasts 7 years, based on 3 hours use per day
- Lasts 10-13 times longer than similar
incandescent
- Replace less often, ideal for hard to reach places
- Lower maintenance and labor costs for lamp
replacements
- 2700°K color temperature closest to
incandescent light
- Quick run-up time
- Instant start, flicker free
- End of Life logic guards against violent failures
- World class phosphor insures high lumen
output and excellent lumen maintenance

Specifications (at full brightness)

End of Life Protection-----	Yes
Ballast Type -----	Electronic
Starting Method -----	Modified Rapid Start
Input Line Voltage -----	120VAC
Input Line Frequency -----	50/60HZ
Lamp Life (rated) -----	10,000 Hours
Ballast Life (rated) -----	50,000 Hours
Color Temperature -----	2700°K
Color Rendering Index -----	84
Minimum Starting Temperature --	-20 ° F
Maximum Operating Temperature --	160 ° F
FCC Compliance -----	Part 18, Subpart C
Lamp Operating Frequency -----	45 KHZ
Lamp Current Crest Factor -----	< 1.60
Maximum Open Circuit Voltage --	600V

ISO 9002
CERTIFIED

2 YEAR
WARRANTY

TCP, Inc.

325 Campus Drive | Aurora, Ohio 44202 | P: 800-324-1496 | F: 330-995-6188 | www.tcp.com

©TCP, Inc. 2008/02475