



# SpringLight™ Specifications

## SpringLight™ Compact Fluorescent

- NPF, 10,000 hours average rated life – SpringLamps®

| Item #      | Item Description                    | CFL Watts | Incandescent Wattage Comparison | Initial Lumens | Color Temperature | Input Line Current | M.O.L. (inches) | Diameter (inches) |
|-------------|-------------------------------------|-----------|---------------------------------|----------------|-------------------|--------------------|-----------------|-------------------|
| 801009      | 9W Mini Spring Light                | 9         | 40                              | 540            | 2700K             | .15A               | 4.0             | 1.8               |
| 8010093     | 9W Mini Spring Light 3 Pack         | 9         | 40                              | 540            | 2700K             | .15A               | 4.0             | 1.8               |
| 80100941 +  | 9 Watt Mini Spring Light 41K        | 9         | 40                              | 440            | 4100K             | .15A               | 4.0             | 1.8               |
| 801009413 + | 9 Watt Mini Spring Light 41K 3 Pack | 9         | 40                              | 440            | 4100K             | .15A               | 4.0             | 1.8               |
| 80100950 +  | 9 Watt Mini Spring Light 50K        | 9         | 40                              | 405            | 5000K             | .15A               | 4.0             | 1.8               |
| 801009503 + | 9 Watt Mini Spring Light 50K 3 Pack | 9         | 40                              | 405            | 5000K             | .15A               | 4.0             | 1.8               |
| 801014      | 14W Mini Spring Light               | 14        | 60                              | 900            | 2700K             | .20A               | 4.4             | 1.8               |
| 8010143     | 14W Mini Spring Light 3 Pack        | 14        | 60                              | 900            | 2700K             | .20A               | 4.4             | 1.8               |
| 80101441 +  | 14 Watt Spring Light 41K            | 14        | 60                              | 800            | 4100K             | .20A               | 4.4             | 1.8               |
| 801014413 + | 14 Watt Spring Light 41K 3 Pack     | 14        | 60                              | 800            | 4100K             | .20A               | 4.4             | 1.8               |
| 80101450 +  | 14 Watt Spring Light 50K            | 14        | 60                              | 630            | 5000K             | .20A               | 4.4             | 1.8               |
| 801014503 + | 14 Watt Spring Light 50K 3 Pack     | 14        | 60                              | 630            | 5000K             | .20A               | 4.4             | 1.8               |
| 801019      | 19W Mini Spring Light               | 19        | 75                              | 1200           | 2700K             | .31A               | 4.4             | 2.3               |
| 8010193     | 19W Mini Spring Light 3 Pack        | 19        | 75                              | 1200           | 2700K             | .31A               | 4.4             | 2.3               |
| 80101941 +  | 19 Watt Spring Light 41K            | 19        | 75                              | 1100           | 4100K             | .31A               | 4.4             | 2.3               |
| 801019413 + | 19 Watt Spring Light 41K 3 Pack     | 19        | 75                              | 1100           | 4100K             | .31A               | 4.4             | 2.3               |
| 80101950 +  | 19 Watt Spring Light 50K            | 19        | 75                              | 840            | 5000K             | .31A               | 4.4             | 2.3               |
| 801019503 + | 19 Watt Spring Light 50K 3 Pack     | 19        | 75                              | 840            | 5000K             | .31A               | 4.4             | 2.3               |
| 801023      | 23W Spring Light                    | 23        | 100                             | 1600           | 2700K             | .38A               | 4.8             | 2.3               |
| 8010233     | 23W Spring Light 3 Pack             | 23        | 100                             | 1600           | 2700K             | .38A               | 4.8             | 2.3               |
| 80102341 +  | 23 Watt Spring Light 41K            | 23        | 100                             | 1500           | 4100K             | .38A               | 4.8             | 2.3               |
| 801023413 + | 23 Watt Spring Light 41K 3 Pack     | 23        | 100                             | 1500           | 4100K             | .38A               | 4.8             | 2.3               |
| 80102350 +  | 23 Watt Spring Light 50K            | 23        | 100                             | 1200           | 5000K             | .38A               | 4.8             | 2.3               |
| 801023503 + | 23 Watt Spring Light 50K 3 Pack     | 23        | 100                             | 1200           | 5000K             | .38A               | 4.8             | 2.3               |
| 801027      | 27 Watt Spring Light                | 27        | 100                             | 1750           | 2700K             | .46A               | 5.5             | 2.4               |
| 8010273     | 27 Watt Spring Light 3 Pack         | 27        | 100                             | 1750           | 2700K             | .46A               | 5.5             | 2.4               |
| 80102741 +  | 27 Watt Spring Light 41K            | 27        | 100                             | 1650           | 4100K             | .46A               | 5.5             | 2.4               |
| 801027413 + | 27 Watt Spring Light 41K 3 Pack     | 27        | 100                             | 1650           | 4100K             | .46A               | 5.5             | 2.4               |
| 80102750 +  | 27 Watt Spring Light 50K            | 27        | 100                             | 1300           | 5000K             | .46A               | 5.5             | 2.4               |
| 801027503 + | 27 Watt Spring Light 50K 3 Pack     | 27        | 100                             | 1300           | 5000K             | .46A               | 5.5             | 2.4               |

- NPF, 8,000 hours average rated life – Globes/A-Lamp/Floodlights

|           |                            |    |     |      |       |      |     |     |
|-----------|----------------------------|----|-----|------|-------|------|-----|-----|
| 8060092 + | 9 Watt G25 Globe 2 Pack    | 9  | 40  | 495  | 2700K | .15A | 4.3 | 3.1 |
| 8060142   | 14 Watt G25 Globe 2 Pack   | 14 | 60  | 800  | 2700K | .23A | 4.3 | 3.1 |
| 8070092   | 9 Watt A Lamp 2 Pack       | 9  | 40  | 450  | 2700K | .15A | 4.1 | 2.2 |
| 8070142   | 14 Watt A Lamp 2 Pack      | 14 | 60  | 800  | 2700K | .23A | 4.4 | 2.4 |
| 802014    | 14 Watt R20 Flood          | 14 | 50  | 495  | 2700K | .23A | 4.3 | 2.5 |
| 803014    | 14 Watt R30 Flood          | 14 | 65  | 645  | 2700K | .23A | 5.4 | 3.7 |
| 8030142   | 14 Watt R30 Flood 2 Pack   | 14 | 65  | 645  | 2700K | .23A | 5.4 | 3.7 |
| 804023    | 23 Watt R40 Flood          | 23 | 120 | 1250 | 2700K | .38A | 6.1 | 4.8 |
| 805023    | 23 Watt Par38 Flood        | 23 | 90  | 1200 | 2700K | .38A | 6.2 | 4.8 |
| 8050232   | 23 Watt Par38 Flood 2 Pack | 23 | 90  | 1200 | 2700K | .38A | 6.2 | 4.8 |

- + Submitted for ENERGY STAR testing.

### Features and Benefits:

- Long life, 10,000 hour average rated life – SpringLamps®
- 8,000 hour average rated life – globes/a-lamp/floodlights
- Lasts 9 years, based on 3 hours use per day
- Lasts 10-13 times longer than incandescent
- Replace less often, ideal for hard to reach places
- Lower maintenance costs for lamp replacements
- Saves up to 75% in energy costs compared to similar light output incandescent lamps
- 2700°K color temperature closest to incandescent light
- Quick run-up time
- Medium base and compact height fits anywhere a standard incandescent fits
- Instant start, flicker free
- End of Life logic guards against violent failures
- World class phosphor insures high lumen output and excellent lumen maintenance
- Up to 23 watts approved for enclosed fixtures

### Applications:

Use anywhere a standard incandescent is used.  
Perfect for: Table Lamps, Floor Lamps, Ceiling Fixtures,  
Wall Sconces, Closet Lights and Desk Lamps

### Specifications (at full brightness)

|                                   |                          |
|-----------------------------------|--------------------------|
| End of Life Protection -----      | Yes                      |
| Ballast Type -----                | Electronic               |
| Starting Method -----             | Modified Rapid Start     |
| Input Line Voltage -----          | 120VAC                   |
| Input Line Frequency -----        | 50/60HZ                  |
| Lamp Life (rated) -----           | 10,000 Hours/8,000 Hours |
| Color Temperature -----           | 2700°K                   |
| Color Rendering Index -----       | 82                       |
| Min. Starting Temperature -----   | -20 ° F                  |
| Max. Operating Temperature -----  | 160 ° F                  |
| U.L. / C.U.L. Listed -----        | Yes                      |
| FCC Compliance -----              | 47 C.F.R. Part 18        |
| Lamp Operating Frequency -----    | 45 KHZ                   |
| Lamp Current Crest Factor -----   | < 1.60                   |
| Max. Open Circuit Voltage -----   | 600V                     |
| Total Harmonic Distortion (NPF) - | < 150%                   |
| Power Factor -----                | >.50                     |



ISO 9002  
CERTIFIED

12 MONTH  
WARRANTY