



Cold Cathode Lamp Specifications

R30 Shaped Cold Cathode Lamps

25,000 Hours
average rated life

Applications:

Replaces less often, ideal for hard to reach places.

Replaces Incandescent for:

- Down Lights
- Recessed Cans
- Track Lights




Special Application Options: (Ordering Suffix)

- 4100K (41K)
- Bulk Packed (BULK100)
- Tip Base (PERM)

Features and Benefits

- Long life: 25,000 hours.
- Cold Cathode lamps are excellent for dimming and rapid cycling applications.
- Special phosphor coating procedure provides excellent color consistency.
- Color coating is resistant to fading and the effects of UV.
- Replaces 40W incandescent lamps, saving up to 25 watts/bulb.
- UL approved for wet location in Base Up position only. Base Up position is defined as screw base in a 12:00 position. Any other base position must be in a UL approved weatherproof fixture.



Catalog Number

Notes

Type



Specifications (at full brightness)

Ballast Type	Electronic
Input Line Voltage	120VAC
Input Line Frequency	50/60HZ
Lamp Life (rated)	25,000 Hours
Color Temperature	2700°K or 4100°K
Color Rendering Index	82
Minimum Starting Temperature	-20°F, -29°C
Maximum Operating Temperature	160°F, 71°C
U.L. / C.U.L. Listed	Yes – E149698
FCC Compliance	Patt 18, Subpart C
Lamp Operating Frequency	45 KHZ
Lamp Current Crest Factor	<1.60
Total Harmonic Distortion	<33%
High Power Factor Rated	>.90

Special Application Notes

- UL approved for wet location in Base Up position only. Base Up position is defined as screw base in a 12:00 position. Any other base position must be in a UL approved weatherproof fixture.

Warranties and Certifications:	Item #	Wattage	Description	Lamp Shape	M.O.L. (inches)	Diameter (inches)	Input Line Current	Initial Lumens	Base Type
 2 YEAR WARRANTY TCP reserves the right to void the warranty for any mis-application of these products.	8R3008CL	8	Cold Cathode R30, Clear	R30	5.3	3.7	.026A	300	E26
	8R3008F	8	Cold Cathode R30, Frost	R30	5.3	3.7	.026A	300	E26
	8R3008P	8	Cold Cathode R30, Pink	R30	5.3	3.7	.026A	N/A	E26